# ON PROVIDING UNIFORM EDGE COMPRESSIVE LOADS FOR WIDE FLAT PLATES

Milan Louis Pittman, Jr.
and
Virgil Willard Rinehart

8854
on spine:

PITTMAN

1954

THESIS
P56

Letter on front cover:

ON PROVIDING UNIFORM EDGE COMPRESSIVE LOADS FOR WIDE FLAT PLATES

MILAN LOUIS PITTMAN, JR.
and
VIRGIL WILLARD RINEHART

# ON PROVIDING UNIFORM EDGE COMPRESSIVE LOADS FOR WIDE FLAT PLATES

by

MILAN LOUIS PITTMAN, JR., LIEUTENANT COMMANDER, U.S. NAVY

B.S., Webb Institute of Naval Architecture (1942)

and

VIRGIL WILLARD RINEHART, LIEUTENANT, U.S. COAST GUARD

B.S., U.S. Coast Guard Academy (1948)

SUBMITTED IN PARTIAL FULFILLMENT

OF THE REQUIREMENTS FOR THE

DEGREE OF NAVAL ENGINEER

at the

MASSACHUSETTS INSTITUTE OF TECHNOLOGY

May 1954

## ABSTRACT

### ON PROVIDING UNIFORM EDGE COMPRESSIVE LOADS FOR WIDE FLAT PLATES

by

Milan L. Pittman and Virgil W. Rinehart

Submitted to the Department of Naval Architecture and Marine Engineering on May 24, 1954 in partial fulfillment of the requirements for the degree of Naval Engineer.

This investigation constitutes a part of a program being carried out in the Department of Naval Architecture and Marine Engineering under the auspices of the Society of Naval Architects and Marine Engineers.

Many merchant vessels are built using a transverse system of framing. These transverse frames, and the more widely spaced longitudinal stiffeners divide the ship's plating into short wide rectangular panels, which are placed either in tension or compression across the short dimension as the ship "hogs" or "sags" under the effects of loading and wave motion. In general the compressive loading is more critical due to the phenomenon of "buckling".

For test purposes these panels can be represented by wide flat plates restrained to varying degrees at their edges and loaded in compression across the short dimension. In this investigation an apparatus was designed for the determination of the buckling and ultimate loads of such plates when all four edges were simply supported (no rotational restraint). This apparatus is intended to accommodate sixteen groups of plates having all possible combinations of the following length-width ratios (a/b) and length-thickness ratios (a/t): a/b = 1/4, 1/3, 1/2, and 3/4; a/t = 30, 50, 70, 90. Only one of these


25070

250720

groups was actually tested, the remainder being left for future completion of the program.

From the work carried out the following conclusions are drawn:

(1) While further work is necessary to make the apparatus completely satisfactory, the equipment designed and built provided reasonably uniform distribution of the compressive load, and a very close approximation of simple support on all four edges of a test plate 56 3/4" in width, 13 5/16" in length, and 5/32" in thickness.

(2) A group of four plates was tested in buckling to augment the evaluation of the test apparatus. From these tests the following tentative conclusions are drawn:

(a) The uniformity of stress distribution is not as critical as was anticipated.

(b) The strength of the plate is not a function of the measured maximum initial unfairness alone, the initial contour and the past history being important also.

(c) For the four plates tested (a/b = 0.237; a/t = 86.4) the experimental critical stresses obtained supported the prediction for the given ratios according to Bleich [8].

Cambridge, Massachusetts
May 24, 1954

Professor Leicester F Hamilton
Secretary of the Faculty
Massachusetts Institute of Technology
Cambridge 39, Massachusetts

Dear Sir:

In accordance with the requirements of the degree of Naval Engineer, we herewith submit a thesis entitled "On Providing Uniform Edge Compressive Loads for Wide Flat Plates".

ACKNOWLEDGMENT

The authors wish to express their deep appreciation of the patient and helpful guidance of Professor C. H. Norris throughout the whole period of this endeavor.

ON PROVIDING UNIFORM EDGE COMPRESSIVE

LOADS FOR WIDE FLAT PLATES

Table of Contents


| | page |
|---|---|
| Abstract | i |
| Letter of Transmittal | iii |
| Acknowledgements | iv |
| Symbols | 1 |
| I Introduction | 3 |
| A. General | 3 |
| B. Research Project | 3 |
| C. Literature Survey | 5 |
| D. Experimental Program | 7 |
| II Procedure | 10 |
| A. General | 10 |
| B. Load Distribution | 10 |
| C. Instrumentation | 12 |
| D. Preparation of Test Plates | 14 |
| E. Evaluation of Test Apparatus | 16 |
| F. Buckling Tests | 16 |
| III Results | 18 |
| A. Equipment Evaluation Tests | 18 |
| B. Buckling Tests | 20 |
| III Discussion of Results | 33 |
| A. Achievement of Uniform Stress | 33 |
| B. Buckling Data | 39 |

Page

Preface iv

Letter of Transmittal iii

Acknowledgements iv

Symbols 1

I Introduction 3

A. History 3

B. Research Projects 3

C. Laboratory Survey 5

D. Experimental Program 7

II Procedure 10

A. General 10

B. Load Distribution 10

C. Instrumentation 12

D. Preparation of Test Piles 14

E. Evaluation of Test Results 16

F. Testing Tools 16

III Results 18

A. Experimental Investigation Tools 18

B. Bending Tests 20

III Evaluation of Results 33

A. Assessment of Testing Methods 33

B. Bending Data 38

page

IV Conclusions 45

V Recommendations 47

Appendixs 48

A. Supplementary Introduction 49

B. Details of Procedure 55

C. Summary of Data and Calculations 77

D. Sample Calculations 79

E. Supplementary Discussion 86

F. Determination of Young's Modulus 91

G. Original Data 94

H. Literature Citations 109

[illegible] [illegible]

[illegible] [illegible]

[illegible] [illegible]

a. [illegible]

b. [illegible]

c. [illegible]

d. [illegible]

e. [illegible]

f. [illegible]

g. [illegible]

h. [illegible]

## NOTATION

| | |
|---|---|
| a | - Unsupported length between centers of loading segments |
| b | - Unsupported length between "a"-edge supports |
| b' | - Actual width of plate |
| d | - Lateral deflection of center of plate from original plane |
| $d_o$ | - Initial lateral deflection of center of plate (zero load) |
| d' | - Distance from point on horizontal center line of plate to reference line |
| k | - Coefficient in buckling formula (based on b/t) |
| K | - " " " " (based on a/t) |
| n | - Number of half waves in buckled plate |
| t | - Thickness of plate |
| w | - Lateral deflection of an arbitrary point on the neutral plane of the plate from the original plane |
| x | - Distance in direction of load (origin at horizontal cl.) |
| y | - " normal to " (origin at one edge) |
| A | - Edge area of plate - b't |
| C | - Arbitrary constant in solution of differential equation |
| D | - Plate constant - $AI/(1-\nu^2)$ |
| E | - Young's modulus of elasticity |
| $E_t$ | - Tangent modulus |
| F | - Friction force in one jack |
| I | - Moment of inertia of strip of plating 1" wide, t thick - $t^3/12$ |
| L | - Same as "a" - used in column formulas |
| P | - Applied load |
| P' | - Load transmitted to test plate |
| $P_{cr}$ | - Critical load |

## Symbols

$a$ = Semi-major length of elliptic cross-section of loading edge

$b$ = Semi-minor length of elliptic cross-section of loading edge

$b_1$ = Larger radius of ellipse

$d$ = Lateral deflection at centre of plate [for circular plate, $d_0$]

$d_0$ = Initial lateral deflection at centre of plate [zero load]

$d_1$ = Deflection due to mechanical applied load at centre of plate [$d - d_0$]

$E$ = Modified Young's Modulus [$E/(1-\nu^2)$]

$E$ = " " " " [$E$ as usual]

$F$ = Function in Airy stress function [$F = \phi r^2/2$]

$G$ = Modulus of rigidity

$H$ = Thickness of plate

$K$ = Lateral deflection at an arbitrary point on the neutral plane of the plate [for circular plate]

$L$ = Thickness in direction of load [height at any point]

$M$ = " normal to " [radius at any point]

$P$ = Edge force of plate = $f'_1 H$

$Q$ = Arbitrary constant in solution of differential equation

$R$ = Plate constant = $EH^3/12(1-\nu^2)$

$T$ = Young's modulus of elasticity

$T_0$ = Tensile modulus

$V$ = Deflection factor in one term

$W$ = Total load [$W = \pi b_1^2 p$ where $p$ = load = $p/\pi b_1^2$]

$Z$ = Ratio of $b_1$ to $a$ - used in column formulae

$\rho$ = Radius of curvature

$\rho_0$ = Initial radius of curvature

$\rho_1$ = Load transmitted to base plate

$\sigma_{cr}$ = Critical load

$P_{ult}$ - Ultimate load

$P_i$ - Internal pressure in jack manifold

$S$ - Force exerted by jack plunger return spring

$\alpha$ - a/b - aspect ratio or width ratio

$\epsilon_{1,2}$ - Measured strains for pair of opposite gages

$\epsilon_e$ - Longitudinal strain at neutral axis of plate

$\epsilon_{av}$ - Average longitudinal strain - P/AE

$f$ - Coefficient of edge restraint ( $f=\infty$ for simple support)

$\mu$ - Micro- (one-millionth)

$\nu$ - Poisson's ratio - assumed to be 0.3

$\sigma$ - Stress intensity

$\sigma_e$ - Longitudinal stress intensity at neutral axis

$\sigma_{av}$ - Average longitudinal stress intensity - P/A

$\sigma_{cr}$ - Critical stress intensity

$\sigma_{ult}$ - Ultimate stress intensity

$\sigma_y$ - Yield stress

$\tau$ - $E_t/E$

# I. INTRODUCTION

## A. General

This investigation represents a part of a more extensive program being sponsored by the Hull Structures Committee of the Society of Naval Architects and Marine Engineers. (See Appendix A.) This project is designed to determine the buckling and ultimate strengths of flat plates of such dimensions and boundary conditions as those usually found in transversely framed merchant vessels.

The framing of a vessel may be considered, for the purposes of such an investigation, as the boundaries of the various panels into which it divides the ship's skin or plating. Each of these panels may be acted upon by direct axial loads, shear forces, and/or moments along either or both edges, and in addition by pressure forces normal to the plane of the plate. Due to the behavior of the plating as a whole, the edges of a particular panel may be considered as simply supported, elastically restrained, or in the extreme condition, clamped. Variables which affect the plating strength are: (1) the ratio of plating length to thickness; (2) the ratio of length to width; (3) the degree of restraint against rotation of the plate edges; (4) the stiffness of panel boundaries, (5) effect of non-uniform distribution of the load.

## B. Research Project

It was felt by the Hull Structures Committee that the experimental data on the strength of these "wide" plates was incomplete and that a considerable range of plating sizes and shapes utilized in ship construction had not been investigated at all. As a specific point, Montgomerie's

## 1a. Summary

This investigation represents a part of a more extensive program being sponsored by the Fuel Conservation Committee of the Society of Naval Architects and Marine Engineers. (See Appendix A.) This project is designed to determine the heating and cooling characteristics of flat plates of most dimensions and boundary conditions as these normally occur in transversely framed merchant vessels.

The framing of a vessel may be considered, for the purposes of such an investigation, as the juncture of the various panels that divide the ship's skin or plating. Each of these panels may be acted upon by different radial loads, shear forcing, and/or moments along edges as well as by a pressure differential on the two sides of the plate. Due to the behavior of the plating as a whole, the edges of a particular panel may be considered as simply supported, elastically restrained, or in the extreme condition, clamped. Particular loads affect the plating strength more: (1) the ratio of yielding length to thickness; (2) the ratio of length to width; (3) the degree of restraint against rotation of the plate edges; (4) the difference of panel temperature, (5) effect of non-uniform distribution of the load.

## 1b. Research Project

It was felt by the Hull Structures Committee that the experimental data on the strength of these "plate" panels was incomplete and that a considerable range of plating sizes and shapes utilized in ship construction had not been investigated as yet. As a specific point, Electromotive's

results [36], based upon tests on plates with unloaded edges free and loaded edges elastically restrained have been applied to conditions where they are not valid, in lieu of better data. Accordingly a research project was formulated which had as its aims the accomplishment of the following four purposes:

Phase I — To make a survey of the literature relating to the theoretical buckling and ultimate strengths and experimental work thereon; to determine the ranges of parameters for which experimental data was lacking or insufficient; and to find information upon the effect and growth of unfairness.

Phase II — To conduct buckling and ultimate strength tests for uniaxial edge compression on plates of such dimensions as are indicated by Phase I, with loaded and unloaded edges simply supported.

Phase III — To conduct buckling and ultimate strength tests for uniaxial edge compression on plates of such dimensions as are indicated by Phase I, with unloaded edges simply supported and loaded edges elastically restrained to varying degrees.

Phase IV — To design, build, and evaluate a test apparatus for the accomplishment of Phases II and III.

It was the original purpose of the authors to complete Phases I, II, and IV. However, due to delays in delivery of the test equipment, and to difficulties encountered in getting the test equipment to function as desired, Phase IV was not completed to the entire satisfaction of the authors. One group of plates under Phase II was tested but its results

are intended primarily to supplement the evaluation of the test equipment under Phase IV.


## 6. Literature Survey

A search of the literature on, or pertaining to, buckling ultimate strength of flat plates under various loadings and edge conditions was made to determine whether adequate theory and experimental data existed pertinent to the range of plate parameters and edge conditions under investigation.

The results of this search led to the belief that theory presented by F. B. Hleich [8] was an adequate, though not mathematically precise, basis for judging the proposed test results, both for buckling and ultimate strength in the elastic and plastic ranges.

The search failed to reveal sufficient experimental data in the region of interest. Shults and Weashler [45] ran five tests at a/b = 1/2 with a/t varying from 20 to 120 with all edges simply supported. Yoshiki 59 also presents similar data skirting the range of interest, with the closest data at a/b = 1/3 and 1/2 but a/t > 108. Figure 1A is provided to indicate the range of interest, the proposed test parameters, and the parameters for which data is presently available.

There is also some possibility that other data found may be revaluated into usable form when considering elastic support of the loaded edges. Various shapes were used as edge restraints but no attempt was made to evaluate the degree of restraint provided.


FIG. 1A
TESTS OF SIMPLY SUPPORTED PLATES IN EDGE COMPRESSION
X - SCHULTZ & WESCHLER
+ - YOSHIKI
O - PROPOSED TESTS
Δ - ACTUAL PLATE SIZES
5/8/54
RANGE OF PARAMETERS FOR TRANSVERSELY FRAMED MERCHANT VESSELS (A.B.S. RULES)
a/b
a/t
0.8
0.7
0.6
0.5
0.4
0.3
0.2
0.1
0
0
20
40
60
80
100
120
140
160
180
200

D. Experimental Program

After considering the region of interest and the points covered by previous investigators it was decided to use sixteen different size test plates having combinations of the following ratios:

$$a/b \quad - \quad 1/4 \;,\; 1/3 \;,\; 1/2 \;,\; 3/4$$

$$a/t \quad - \quad 30 \;,\; 50 \;,\; 70 \;,\; 90$$

These particular values were chosen for the following reasons:

1. Within the region of interest there has been very little data obtained, and the theory has not been confirmed.

2. Some of the a/b values lie above the region outlined by the American Bureau of Shipping Regulation, since the ABS values are for plates near the midship section, and the plates farther forward or aft have higher a/b ratios.

3. For extremely low a/b ratios, repeatable results are difficult to obtain, and it was decided to concentrate on getting usable results for the intermediate values.

4. Higher a/b ratios are of interest primarily for longitudinally framed ships.

Actual sizes for the test specimens were decided upon after consideration of the following factors:

1. The a/b, a/t ratios decided upon above.

2. In order to use existing equipment previously used in investigations by Polychrone [10] and Capozzoli [12], the sum of one of each short dimension chosen was not to exceed 34".

3. The long dimensions were calculated from the short dimensions and the a/b ratios selected above.

4. The maximum plate thickness which could be accomodated by the

"a-edge" supports was 5/16". In addition it was desirable to use standard plate thicknesses.

5. Since it was desired to obtain both buckling and ultimate strengths, the plates should fail under a load less than the capacity of the testing machine (300,000 pounds).

6. The "a" and "b" dimensions, as determined above were then altered as follows:

(a) The "a" dimension was decreased by 3/4" since it was believed at this time that the loading segments which transmitted the load would act as a part of the effective length of plate. (It was later decided that this was not the case, and hence the actual a/b and a/t values were not exactly the same as had been selected.) The actual plate dimensions are given in Table I.

(b) The "b" dimension was increased by 1/2" to allow 1/4" extension beyond the line of ball bearing support at each unloaded edge.

TABLE I

Plating Dimensions

| Nominal a/b | | Nominal a/t 30 | 50 | 70 | 90 |
|---|---|---|---|---|---|
| 3/4 | l | 6.750 | 10.188 | 10.188 | 13.313 |
| | w | 10.500 | 15.080 | 15.080 | 19.25 |
| | t | 1/4 | 7/32 | 5/32 | 5/32 |
| | a/b | .675 | .699 | .699 | .710 |
| | a/t | 27.0 | 46.5 | 65.2 | 85.2 |
| 1/2 | l | 6.750 | 10.188 | 10.188 | 13.313 |
| | w | 15.500 | 22.375 | 22.375 | 28.625 |
| | t | 1/4 | 7/32 | 5/32 | 5/32 |
| | a/b | .450 | .465 | .465 | .474 |
| | a/t | 27.0 | 46.5 | 65.2 | 85.2 |
| 1/3 | l | 6.750 | 10.188 | 10.188 | 13.313 |
| | w | 23.000 | 33.513 | 33.513 | 42.688 |
| | t | 1/4 | 7/32 | 5/32 | 5/32 |
| | a/b | .300 | .310 | .310 | .316 |
| | a/t | 27.0 | 46.5 | 65.2 | 85.2 |
| 1/4 | l | 6.750 | 10.188 | 10.188 | 13.313 |
| | w | 30.500 | 44.25 | 44.25 | 56.75 |
| | t | 1/4 | 7/32 | 5/32 | 5/32 |
| | a/b | .225 | .233 | .233 | .237 |
| | a/t | 27.0 | 46.5 | 65.2 | 85.2 |

## II. PROCEDURE

### A. General

The analysis of the behavior of flat plates is based upon a given stress distribution, in this case the distribution of the force applied at the loaded edges. The problem, then, was to provide a means of applying a uniformly distributed edge load and at the same time to maintain simple support at the loaded edges, so that the edges of the plate were allowed complete freedom of rotation and freedom of translation in the plane of the plate while being restricted from any lateral movement.

### B. Load Distribution

A uniform load distribution can be obtained by one of two methods, either by causing a uniform contraction in the plane of the plate, or by applying a load which is distributed by some external system. Either of these methods provides the desired loading condition prior to buckling of a perfectly flat plate. In the case of a plate in a ship's structure, the assumption that the "loaded" edges of a panel remain straight (uniform deflection loading) is probably closer to the actual situation than is the assumption of a uniform load distribution. However for reasons given below, this method of loading is very difficult to use.

The available testing machine, shown in Fig. 34, has an upper loading head which is a hollow cylindrical forging approximately 18" outside diameter, and 11" inside; the lower head is 24" square. Since the largest plate is 56 3/4" wide, some auxiliary device was necessary to distribute the load to the plate. Preliminary calculations indicated that an I-beam

which would limit the diminution of the stress near the ends of the plate to a nominal value, say 5% of the average, would be of prohibitive size. This analysis is borne out by the fact that the constant deflection heads of the testing machine at the David Taylor Model Basin are extremely deep.

The solution commensurate with the time and money available was the use of a system of seven 20-ton Blackhawk Porto-Power hydraulic jacks connected to a common manifold, identical systems being used at both the top and bottom of the plate. The testing machine transmitted the load through an 18-inch wide flange I-beam to the jacks which in turn applied the load to the plate through the arrangement intended to provide simple support. This system, while not exactly reproducing the practical situation, provided a solution which was feasible, and gave known conditions of loading.

Bridging the gaps between the jacks was a 3/4" x 3-5/8" x 5' bar of AISI C-1045 steel hardened to 50 Rockwell C. The purpose of this bar was to further distribute the load between the jacks when they were widely separated, and served as a bearing surface against which the loading segments bore. The bar was ground flat on one side, and on the other had a shallow groove ground to allow two alternative ways of using the bar.

The loading segments transmitted the load from the loading bar to the plate itself. These segments were cut from 3/4" diameter drill rod which had a longitudinal groove milled to center depth; the rod was then cut to lengths of 7/8" and 1/2", the shorter segments being placed at the end of the plate. These segments were hardened to a hardness comparable to that of the loading bar. These segments transmitted the load along a radius to the edge of the plate. In this way torsional restraint along

the plate edge was negligible, the plate edge was free to rotate, and the sliding friction and/or the groove in the loading bar prevented lateral movement of the plate edges. It is believed that a very close approximation to simple support was achieved.


In the design of the segments, sufficient clearance was allowed in the milled slot so as to reduce the probability of a notch failure at the internal corners. To reduce the amount of eccentricity of loading, shimming strips 0.017 inches thick were inserted between the plate sides and the segments. (See Figure 27.)

After the first test showed that the load distribution was quite erratic, a gasket of neoprene was inserted between the plate edges and the loading segments for the purpose of eliminating local hard spots. In later tests gaskets of 3/32" and double 1/16" diameter rosin core solder were used for this same purpose. Although the problem of hard spots was not completely solved by this means, it was reduced so as to indicate the use of the gaskets was beneficial.

C. Instrumentation

To obtain the required strain measurements, Type A-3 SR-4 electric strain gages were mounted on opposite sides of the plate at the center of the plate, and in some cases at additional locations along the horizontal center line. For the purpose of determining the distribution of the applied load, gages were also mounted along the top and bottom edges as close to the edge as possible to measure the least favorable distribution. (See Fig. 18.) A four-arm Wheatstone bridge having as active gages, the gage on the plate and a compensating dummy gage on an unloaded plate of the same thickness, was used; the strains were read on a Baldwin

FIG.
TEST PLATE
No. 1




Details of Locations of Jacks & Strain Gages

Note: Even numbered gages on opposite side

Type K (or L) Strain Indicator. Strain readings could be read to ± 2 microinches/inch. Although the accepted accuracy is ± 5 microinches/inch, differences of ± 10 microinches/inch between initial and final zero readings were not uncommon, and occasional shifts of greater magnitude were recorded. However, in most cases the zero shift was from 0-8 microinches/inch.

Lateral deflections were measured by an Ames dial gage with a range of 0.500 inch, mounted so as to slide along a planed angle iron at the horizontal center line of the plate. (See Figs. 30 and 32.) The dial gage itself was accurate to within ± 0.001 inch. However, even though the angle upon which the gage was mounted was calibrated when the system was unloaded, no attempt was made to check whether or not it deformed any when the system was loaded.

The total load applied was measured on Massachusetts Institute of Technology testing machine No. 105, a hydraulic installation built by Southwark-Emery with a capacity of 300,000 pounds. On the lower scale (0-30,000 pounds) loads could be read to ± 10 pounds, and when the machine was used to apply the load, the load could be maintained to ± 50 pounds of the desired value. When the hand pump was used to apply the load, comparable accuracy could be obtained, the load readings being taken on the testing machine.

As an additional check on the total load, a Babcock and Wilcox gage with a range of 0-1000 psi was used to measure the pressure at the manifold of the upper jack system for some tests.

## D. Preparation of Test Plates

The test plates were provided by Bethlehem Steel Co., Shipbuilding

Division, Quincy, Mass. They were laid out in the same direction and cut from a single steel plate. Of the sizes of plates for which the apparatus was designed it is considered that the group of plates with the lowest aspect ratio (1/4), i.e., those having the longest loaded edge, presented the most difficult problem in securing a reasonably uniform load distribution. Hence this group of four plates was selected to evaluate the apparatus. The opposite edges of all test plates were planed parallel to each other.

In order to mount strain gages on the plates it was found expedient to sand-blast or shot-blast these plates in order to remove the mill scale. One of this group of plates, Plate No. 1, was selected and instrumented along both edges as shown in Fig. 1B. SR-4 type A-3 strain gages were mounted close to each loaded edge so as to fall under and in between each of the jacks. Gages were mounted in opposite pairs on both sides of the plate and connected so each gage could be read individually. Hence both bending moments and direct stress can be found. Plate No. 2 was instrumented with five pairs of gages located on the center line of the plates along the "b" dimension as shown in Fig. 2B. Plates Nos. 3 & 4 each have one pair of gages located at the center of the plate.

Due to the shearing, machining, and blasting, the test plates were slightly curved in both directions. This curvature was minimized as far as practicable by subsequent rolling. It was found that the curvature remaining in the long direction could be straightened by inserting blocking between the plate and the angles connecting the "a"-edge supports. These blocks were removed before the first readings were taken. When the grooved side of the loading bar was used, this was not necessary. The curvature along the shorter dimension is treated as an initial unfairness.

During the first run on Plate No. I (Fig. 18) the specimen was inadvertently buckled and an ultimate load of 35000 pounds was recorded. At this time it was expected that this ultimate load would be higher. Hence it was necessary to re-straighten Plate No. I before further testing could proceed. This was accomplished successfully using the testing machine as a press.

E. Evaluation of Test Apparatus

A total of eighteen tests on Plate No. I were run with the test apparatus to determine the load distribution. In each of these tests some detail of the loading system was changed, such as the jacks (with or without), loading bar, gasket, shimming, or loading segments. In all of these tests the same plate was used since a total of 60 gages were installed on it for this purpose and it was not practical to instrument more plates this fully. In each test a load of about 20,000 pounds was applied and held for several minutes to set the gasket. The load was then removed, and re-applied in progressive steps, gages being read at several values of the load.

F. Buckling Tests

Buckling tests were made on the plate used in part D above, and on three other plates of the same size. It should be pointed out that these tests were made to augment the evaluation of the machine and not primarily to obtain buckling data.

In each of the buckling tests, the load was applied by means of a hand pump connected to the manifold of the upper jack system. Zero readings of the strain gages were taken when the plates were in place

ready for testing but before any load was applied. The load was applied in increments of 2000 pounds and strain gage readings taken. At certain loads further readings were taken for gages other than those giving buckling data in order to check the load distribution. Some lateral deflections of the plate were also recorded.

To obtain the ultimate load, the lower head of the test machine was moved up until the load began to decrease. This was taken as the ultimate load.

## III. RESULTS

### A. Equipment Evaluation Tests

#### 1. General

The results of evaluation tests run on test plate No. 1 (see Fig. 1B) are presented graphically in Figures 1 to 20 inclusive. These plots depict average strain readings 1 1/4" from each loaded edge of the plate under and between each hydraulic jack position along the "b" edges. Original data and sample calculations on selected tests are given in Appendices C and D respectively.

To supplement the abbreviated description of the test on each of the Figures 1 to 20 inclusive there is presented here a code of test description. A more detailed description will be found in Appendix B.

#### 2. Code of Test Description

a. Load Application

(1.) Machine - Load applied with 300,000 # hydraulic testing machine, No. 105, Testing Materials Laboratory.

(2.) Pump - Load applied with hydraulic hand pump through top system of jacks.

b. Jacks

(1.) Seven 20-ton hydraulic jacks on each edge as shown in Fig 27 and connected to a common manifold. (Fig. 30).

c. No Jacks

(1.) All jacks removed. Loading bar bearing directly on I-beams.

d. Bar - Loading Bar

(1.) 3/4" - Designates hardened steel bar 3/4" x 3 5/8" See Fig. 27.

(a) (F) - Flat side of bar toward loading segments.

(b) (G) - Grooved side of bar toward loading segments.

(2.) 1/16" - Designates thickness of cold rolled steel bar - 1 1/2" wide.

(3.) 1/4", 5/16", 3/8" - Designates thickness of cold, rolled steel bar 1 1/4" wide.

e. Gasket - Description of gasket material between edge of test plate and loading segments

(1.) Neoprene - 1/16" x 1/8" cut from neoprene sheet.

(2.) Solder - strip cut from roll of resin core solder.

a) 3/32" - Diameter. Single strip per edge of plate

b) 1/16" - Diameter. Double strip side by side per edge of plate

f. Shims

(1.) 0.017" shim stock inserted between each side of segment groove and side of test plate. Remaining clearance $\approx$ 0.003"

g. No Shims

(1.) Shims removed. Clearance between segment slot and plate approximately 0.035".

h. Load

(1.) Gage reading of 300,000 # testing machine.

i. Test Plate Orientation

(1.) Orientation indicated by showing location by number of end gages on the test plate.

j. Computed Strain

(1.) Average computed strain for a load of 10,000 lbs., 40.3 micro inches per inch, is shown as a horizontal dashed line.

B. Buckling Tests


Four plate specimens were tested to ultimate failure in the testing apparatus. Results of the tests are shown in Table II and Fig. 21.

Deflections and strain gage readings are shown in Appendix H.

The failure of each plate was observed to be one noded in both a and b directions.

In each test the load was applied with the hand pump and shims were inserted between the plate and leveling segments. Plates 1 & 2 were tested with double 1/16" diameter solder gaskets and with the flat side of the 3/4" loading bar toward the segments. Plates 3 & 4 were tested with single 3/32" diameter solder gasket with the grooved side of the 3/4" bar towards the loading segments.


FIG. 1




TEST NO. 1
PLATE NO. 1
Load - 10,000 lbs.

Machine Loaded Hyd. Jacks (9)
Segments, No Shims
3/4" Bar (G), No Gasket

FIG. 2





5/1/54 VMK

TEST NO. 2
PLATE NO. 1
Load - 10,000 lbs

Machine Loaded Hyd. Jacks (9)
Segments, No Shims
3/4" Bar (G), Neoprene Gasket


FIG. 3




TEST NO. 3
PLATE NO. 1
Load - 10,000 lbs.

Machine Loaded Jacks (4)
Segments, No Shims
3/4" Bar (G), 3/32" Solder Gasket


FIG. 4




TEST NO. 4
PLATE NO. 1
Load - 10,000 lbs.

Machine Loaded Hyd. Jacks
Segments, No Shims
3/4" Bar (F), Re-used Gasket
FROM Test No. 3


FIG. 5




TEST NO. 5
PLATE NO. 1
Load - 10,000 lbs.

REPEATABILITY TEST
SAME Conditions as Test No. 4 except for new gasket


FIG. 6




5/11/54 VHR

TEST NO. 6
PLATE NO. 1
Load - 10,000 lbs.

Repeatability Test
Same Conditions as Nos. 4 & 5
Same gasket as Test No. 5




TEST NO. 7
PLATE NO. 1

Load - 10,000 lbs


Machine Loaded Hyd. Jacks
No Segments, No Shims
3/4" Bar (F), Sheet Lead Gasket
(1/16") - 2 in. wide

TEST NO. 8
PLATE NO. 1

Load - 10,000 lbs

Repeatability Test
Same Conditions as Test No. 7
except for new gasket
1/16" - 1 1/4" wide

## FIG. 9





TEST NO. 9
PLATE NO. 1

Load - 10,000 lbs.

Machine Loaded Hyd. Jacks
Segments, Shims
3/4" Bar (F), 3/32" Solder Gasket

## FIG. 10





TEST NO. 10
PLATE NO. 1

Load - 10,000 lbs.

Same Conditions as Test No. 9
except for replacement of
3/4" Bar with 1/16" x Strip

FIG. 11





TEST NO. 10
PLATE NO. 1

Load - 10,000 lbs.

Machine Loaded Hyd. Jacks (1) Segments, Shims 1/16" Strip; 3/32" Solder Gasket

FIG. 12





5/1/54 VmR

TEST NO. 11
PLATE NO. 1

Load - 10,000 lbs.

Conditions same as for Test No. 10, except load applied by hand pump.


FIG. 13




TEST NO. 12
PLATE NO. 1
Load - 10,000 lbs.

Pump Loaded Hyd. Jacks (1) Segments, Shims 1/16" Strip, Double 1/16" Solder Gasket


FIG. 14




TEST NO. 13
PLATE NO. 1
Load - 10,000 lbs.

Pump Loaded Hyd. Jacks (1) Segments, Shims 3/4" Bar (F) Re-used Gasket from Test No. 12

FIG. 15





TEST NO. 12
PLATE NO. 1

Load - 10,000 lbs.

Pump Loaded Hyd. Jacks (1) Segments, Shims 1/16" Strip, Double 1/16" Solder Gasket

FIG. 16





TEST NO. 14
PLATE NO. 1

Load - 10,000 lbs.

Pump Loaded Hyd. Jacks (1) Segments, Shims 3/4" Bar (F), New Double 1/16" Solder Gasket

FIG. 17





TEST NO. 15
PLATE NO. 1

Load - 10,000 lbs.

No Jacks
Segments, Shims
3/4" Bar (F), Re-used Gasket from Test No. 14

FIG. 18





5/1/54 JMK

TEST NO. 16
PLATE NO. 1

Load - 10,000 lbs.

Repeatability Run. Conditions same as for Test No. 15, except for new double solder (1/16") gasket.

FIG. 19





TEST NO. 17
PLATE NO. 1

Load - 10,000 lbs

Pump Loaded Hyd. Jacks
Segments, Shims
Top Bar - 5/16" x 1 1/4", New 2-1/16"
Bot. Bar - 1/4" x 1 1/4" Solder Gasket

FIG. 20




5/1/54 VMR

TEST NO. 18
PLATE NO. 1

Load - 10,000 lbs

Pump Loaded Hyd Jacks
Segments, Shims
Top Bar - 3/8" x 1 1/4", Re-used Gask.
Bot. Bar - 1/4" + 5/16" fm. Test No. 17

TABLE II

RESULTS of BUCKLING TESTS

Plate Data: a/b 0.237

a/t 86.5 (av)

E 28,300 kips/in.$^2$

Material: Mild steel (1020 ship plate)

Boundary Conditions: Simple support on all four edges.

| Plate No. | Critical Strain Gage Location from Plate Center* | Initial Deflection (inches) | t (inches) | Ultimate Load (Kips) |
|---|---|---|---|---|
| 1. | 8.04" left<br>1.32" up | 0.085 | 0.1535 | 35.0<br>36.2 ** |
| 2. | 10.06" left on center line | 0.057 | 0.1545 | 29.5 |
| 3. | at center | 0.009 | 0.1545 | 32.5 |
| 4. | at center | 0.071 | 0.1540 | 33.5 |

* Pair of gages on opposite sides of the plate and nearest the maximum deflection of plate under load. Long axis of plate is horizontal.

** Ultimate load after re-straightening and after many stress cycles to loads below the ultimate.

## Table II

### Location of Precision Gauges

Plate Gauge: Wyb 0.572

Wyb 50.2 [psi]

E 14,200 kips/in.$^2$

Material: Mild steel (1020 mild plate)

Boundary Conditions: Simply supported on all four edges.

| Plate No. | Location from Plate Center | Central Element Deflection (inches) | E (inches) | Difference Load (kips) |
|---|---|---|---|---|
| 1. | 6.0" left | 0.800 | 0.1212 | 50.2 ** |
| | 3.25" up | | | |
| 2. | 10.00" left on vertical line | 0.807 | 0.1215 | 49.5 |
| 3. | At center | 0.800 | 0.1212 | 50.2 |
| 4. | At center | 0.672 | 0.1164 | 33.3 |


* Tube of paper on opposite ridge of the plate was removed

One maximum deflection of plate under load. Loop hole of

plate is horizontal.

** Eliminate load after re-centering and after each strain

cycles to loads below the eliminate.


FIG. 21
AVERAGE STRESS VS. STRAIN DIFFERENCE
5000
4500
4000
3500
3000
2500
2000
1500
1000
500
P/A
p.s.i.
0
1000
2000
3000
4000
5000
ε2 - ε1 , Micro in/in
O - PLATE NO. 1
□ - PLATE NO. 2
Δ - PLATE NO. 3
▽ - PLATE NO. 4
4/3/54

## IV. DISCUSSION OF RESULTS

### A. Achievement of Uniform Stress

#### 1. General

Figures 1 to 20 represent the results of an effort to obtain an acceptable stress distribution along the loaded edge of the test plate. Test No. 1 (Fig. 1) indicated immediately that the equipment was not performing as desired. The values of the average strains did however tend to vary about the mean calculated strain indicated by the dashed line in Figs. 1 to 20 inclusive. Subsequent tests are attempts to isolate various causes for the wide variation in strain. It must be admitted that the results of these further tests were not completely satisfactory. Fairly wide strain variation continued to exist in all of the tests. A summary of comparison of average observed to average computed strains and percent deviation for the various tests appears in Table IIIA, Appendix C. It may be said however that in general the average line of the plotted distribution of the observed strains remained parallel to the loaded edge. The necessity of using the hydraulic jacks has not been clearly demonstrated here. Test Nos. 15 & 16 (Figs. No. 17 & 18) show scatter not far different from other tests except that a load concentration appeared on one "a"-edge. Such results however depend on the accuracy to which the L-beams can be shimmed into a parallel position. Under heavier loads that were not needed in these tests but which will be required for completion of the testing program, the local stress concentrations produced by the beam shims may affect the L-beams locally and destroy the original alignment. Such action was actually observed when the L-beams were originally set up and placed in

## IV. RESISTANCE OF BRIDGES

### A. Additional Bridging Degrees

#### 1. General

Figures 2 to 13 represent the results of an attempt to obtain an empirical curve distribution along the tested edge of the test plate. Each is plotted for 1 (Fig. 2) indicated immediately this the equipment was performing as desired. The values of the strength obtained by the tested line in Figs. 2 to 13 inclusive. Theoretical tests are although in tactics numbers assume for the side ventilation in steels. It must be admitted that the results of these fourteen tests were not completely satisfactory. Fairly wide private variations occurred to exist in all of the tests. A necessary of comparison of strength observed in several computed objective and personal deviations for the various tensile strength in Table XIII, Appendix C. It may be said however that in general the average line of the plotted distribution of the theoretical stresses remained parallel to the lowest edge. The necessity of using the hydraulic jacks has not been clearly demonstrated there. Test Nos. 12 A 12 (Figs. No. 12 A 12) show another and the difference from other tests except that a load concentration appeared at one 1/4-edge. Test results however depend on the capacity to which the 1-beam may be obtained into a practical position. Other interior loads tests were not carried to those limit but which will be required for completion of the bending program. The local stress concentrations produced by the bore holes may affect the 3-beam locally and destroy the vertical alignment. That action was noticed observed when the 3-beam were originally set up and placed in

position. Also, the loads used in this part of the project were not severe enough to materially deflect the L-beams. It is this deflection which the use of the jacks was designed to overcome. It was expected that on the plates with shorter "b" edge dimensions, the use of jacks would not be necessary. Based on the results of this thesis, it is felt that no conclusive statement on the future use of the jacks should be made.

2. Strain Gage Locations

The strain gage locations on Test Plate No. 1 (Fig. 18) were placed as close to the edge of its plate as practicable as it was expected that at this location the strain variation would be a maximum. Due to the wide variations in strain observed, it is believed that further strain readings are needed from more closely spaced gages between jack positions in order to trace the reasons for these variations. It should be pointed out that where the 3/4" loading bar is used, peak strain readings do not always fall under jack locations. Also the jack foot itself (see Fig. 27) is not solid across the loading face. This may give rise to some strain variations especially when lighter loading bars are used.

It is expected that the strains at the middle of the test plate would be considerably moderated through shear action even when varying adjacent strains are recorded near the loaded edges. It is the strain at or near the center of its plate that is of primary interest when tests or buckling are performed. Further experiments should be performed to determine the validity of this assumption.

3. Performance of Hydraulic Jacks

It is known that two factors are present which could affect the

uniformity of action of the hydraulic jacks. Friction forces may vary from jack to jack and probably vary considerably within one jack with changing loads. The plunger return springs in each jack may not produce identical return forces. For normal jack usage, the uniformity of the plunger return springs is of little consequence, hence it cannot be assumed that the manufacturer has taken special care to obtain such uniformity.

The results of Tests 3 to 6 (Figs. 3 to 6) could indicate that the lower jack system was performing better than the upper system since the variations in strain always appeared to be less on the lower plate edge. In order to check this indication and to check the jack performance as a whole, Tests Nos. 10 to 12 (Figs. 10, 12, & 13) were run with a loading bar 1/16" in thickness. This bar merely served to hold the loading segments in place between the jacks. Very little load distribution by this bar was expected or found. Referring to Fig. 13 it would appear that the jacks functioned uniformly. When considering that the possible error in each of the strain points plotted is of the order of ± 5 microinches per inch, these results are excellent evidence that the jacks are functioning properly. The low order of the readings compared to the computed average strain has no particular significance here since the strain readings under each jack location are also under the hollow part of the jack foot. Maximum readings would occur about one and one-half inches on either side of the present gage location depending precisely on the relative position of each segment in the critical area.

4. Effects of Gaskets

A comparison of Figs. 1, 2, 3, & 16 can be made to study the effect

of placing gasket material along the loaded edges of the plate. From Figs. 1 & 2 it can be seen that the use of a neoprene gasket materially reduced the strain variation. Comparing Fig. 3 with Fig. 2 it appears that the use of a single solder wire gasket further reduces these variations to a small extent. Figs. 3 and 16 show little change resulted from using a double rather than a single solder strip. This comparison is complicated by the fact that the flat side of the loading bar was used in Fig. 16.

It seems evident that part of the strain variations are due to local unevenness in the plate or loading bar and that the effect of these points on the strain distribution can be reduced through the use of a gasket material. The solder gasket appears to be slightly more beneficial than a neoprene gasket although this difference may have disappeared entirely if a thicker neoprene gasket were used. The results also tend to indicate the advisability of using new gasket material for each test.

5. Size and Shape of the Loading Bar

A comparison of Figs. 15 and 16 indicated that the presence of the 3/4" thick loading bar quite logically tends to bridge the gap between the points of load application under each jack but in so doing introduces local strain variation of considerable magnitude.

An attempt was made to determine if an optimum bar size existed between the two extreme sizes used in Figs. 15 and 16 by inserting bars of intermediate size. (See Figs. 19 & 20.) The results of these tests seem to indicate that the thicker bar should give better results but that the 3/8" x 1 1/4" bar gives acceptable results. Since the plate tested uses the widest jack spacing of all the plates in the test program,

difficulties of bridging the gap between jacks will decrease on the remaining plates.

When using the 3/4" loading bar a choice existed on which face to use, flat or grooved. During the early tests it was felt that the position of the segments in the groove may have given rise to local strain variations. Hence, the flat side of the bar was used in subsequent tests. A comparison of Figs. 3 & 4 however shows that little difference in strain variation can be attributed to this effect. Actually during the buckling tests, it was found that it is necessary to use the grooved side of the loading bar to prevent lateral movement of the loaded edges when high deflections occur.


6. Effect of Shims

A study of Figs. 4, 5, 9, & 16 seems to indicate that the presence of shims has little effect on the strain variation. However it is felt that shims are necessary when conducting buckling tests. The milled grooves in the loading segments are approximately 1/32" wider than the plate thickness. The presence of the shims decreases the possibility of eccentric loading on the plate by insuring that the plate edge is centered at or under the radial center of the loading segment. It further aids in straightening the plate edge when the grooved side of the loading bar is used.

7. Effect of Loading Segments

Two tests (Figs. 7 & 8) were run without segments but with a sheet lead gasket between the plate and the loading bar. Strain variations for these tests were generally worse than for other comparable runs. It is


FIG. 22




TEST NO. 19
PLATE NO. 1
LOAD - 20,000 lbs.

Buckling Test
Pump Loaded Jacks, Segments,
Shims, 3/4" Bar (F), Double 1/16" Solder

FIG. 23




TEST NO. 20
PLATE NO. 2
Load - 20,000 lbs.

Buckling Test
Pump Loaded Jacks, Segments,
Shims 3/4" Bar (F) Double 1/16" Solder

difficult to separate the effects of the change in gasket material and the effect of the segments. The combination of effects however causes higher strain variations. It was felt that the gasket material used here (lead roof flashing) seems too stiff a material and its effect masked that of the segments.

B. Buckling Data

1. General

The comparison of the critical stress of the plate specimens with that of the theoretical predictions (See Table IIIB) was most gratifying and constituted an important phase in the overall evaluation of the test equipment. Although evidence of a concrete nature is lacking these results tend to support the view that both the stress distribution and the achievement of simple support on the plate edges was satisfactory at least to a practical degree. Further tests should be run to support this view. In particular a separate test perhaps without "a"-edge supports should be run to check the action of the segments to determine if rotational restraint is present. It is felt that fairly high loading would have to be developed before any appreciable resisting moment could develop.

The results of the buckling tests do not completely allay the apprehensions developed under the discussions of uniform edge loading. These results do, however, provoke the thought that the degree of uniformity necessary for uniform buckling results is not as stringent as heretofore supposed.

2. Effect of Initial Deflections


It will be noted in the results (Table II), test Plate No. 1 failed

at a considerably higher load than the remaining specimens. It should also be noted that the original ultimate load before the plate was straightened was 1200 lbs. lower than the final ultimate load. Unfortunately too few strain readings were recorded preceding the first ultimate load on which to base an estimate of the critical load. It is believed however that the difference in the first and final ultimate loads can be explained at least in part by the fact that in restraightening the plate, a complex contour of the plate surface was introduced. It is believed that the strength of such a plate is increased depending on the amount and character of the departure of the initial unfairness from the final deflected shape of the plate prior to yielding. With simple support such shape is usually sinusoidal in form. No particular correlation between initial maximum deflection and final ultimate or buckling loads could be found with the remaining plates. This tends to support the belief that in thin plates character of the initial contour is an overriding effect when considering the strength of such plates.

3. Action of Wide Thin Plates Under Edge Compressions

A comparison of Euler's column formula and the solution of the plate equation for the critical stress indicate that the only difference in form except for the Poisson effect in plates is the value of "k" in the solution for plates. For wide plates this value is very close to one. Hence one would expect wide plates to behave very much like columns up to the critical stress. An inspection of Figs. 24, 25, & 26 indicates that its test plates behaved very much like eccentrically loaded columns where the deflection grows continually under increasing load. Under such conditions it is somewhat an artificiality to attempt to define a critical

FIG. 24
STRESS VS. STRAIN DIFFERENCE





DETERMINATION OF $\sigma_{CR}$ BY TOP-OF-THE-KNEE METHOD

5/13/54 MH

FIG. 25


STRAIN DIFFERENCE - LOAD RATIO VS. STRAIN DIFFERENCE




DETERMINATION OF $\sigma_{cr}$ BY SOUTHWELL'S METHOD

5/14/54 MWC

FIG. 26
LOAD VS. LOAD-DEFLECTION RATIO



buckling load. However the necessity exists if comparison to the theoretical buckling stress is to be made. The significant load however, in this case is the ultimate load, the occurence of which is probably coincidental with the development of a plastic hinge in an element of the plate. Bleich [Ref. 8, p. 475] gives a predicted value for the ultimate stress in wide plates based on Marguerre's large deflection theory. Such predicted values based on $\sigma_y$ and $\sigma_{cr}$ lead to absurd values for the plates tested since the assumption that the plate remains a rectangle is not valid for these plates. It is believed however that Bleich's predicted values of the critical stress for the remaining plates in the test program will be extremely valuable in alerting the experimentor to impending failure. It should be noted that the authors failed to obtain a sufficient number of readings just prior to the ultimate load on the plate. The character of the load-deflection near failure plays a large part in determining the theoretical value of the critical stress.

4. Calibration of the Testing Machine (See Appendix E).

While this topic is not strictly in the nature of a result it does have a bearing on the validity of the comparison of buckling results. The difference between the load indicated by the testing machine and that indicated by the hydraulic jack pressure at the manifold does not necessarily prove an error exists but it does admit the possibility of such an error. It is expected however that any correction if required will be small since the three gages on the machine agree very closely. Before future testing proceeds however, the testing machine should be calibrated.

calibrated.

Before future testing proceeds however, the testing machine should be modified since the three gages on the specimen agree very closely, enough so error. It is expected however that any correction if required necessarily prove an error unless but it does admit the possibility of that indicated by the ignorable 3per pressure or the specimen does not The difference between the load indicated by the testing machine and have a bearing on the validity of the comparison of bending results.

4. Calibration of the Testing Machine (See Appendix B).

While this study is not entirely in the opinion of a result is deem

value of the critical stress.

deflection tube. Failure plate a large part in determining the theoretical prior to the ultimate load on the plate. The observation of the bindfind the extreme fibers failed to obtain a sufficient number of readings just alerting the experimenter to impending failure. It should be noted remaining places on the test program will be extremely valuable in however that Bleich's predicted values of the critical stress for the plate remains a rectangle is not well for these plates. It is believed to showed values for the plates tested since the assumption that the for the ultimate stress in wide plates based on Timoshenko's large deflection theory. Such predicted values based on $D_y$ and $D_{xy}$ are used element of the plate. Bleich [Ref. 6, p. 491] gives a predicted value partially coincidental with the development of a plastic hinge in an over, in this case in the ultimate load, the occurrence of which is theoretical buckling stress is to be made. The significant load bu-

## V. CONCLUSIONS

1. The load distribution provided by the test apparatus is not completely satisfactory; however certain lesser conclusions can be drawn.

   a. The hydraulic jacks functioned as they were expected to, although there is not enough data at present to conclude they are necessary.

   b. There was no general slope to the mean line of strain distribution; rather the strains varied about the computed average value.

   c. The stiffness of the loading bar is an important factor in the load distribution and one which is subject to more study.

   d. Factors other than the jacks produced serious strain variations as is evidenced by the fact that the strain peaks showed no consistent tendency to occur under the jacks when the heavier bars were used.

   e. Load distribution is not markedly influenced by type of gasket and whether or not shims are used; however a new gasket should be used for each test and shims should be used to reduce eccentricity of loading.

2. Although no specific investigation was made, it is tentatively concluded that simple support was obtained, in view of the following observations:

   a. The final buckled configuration.

   b. The fact that the edges remained straight even after buckling, especially when the grooved bar was used.

   c. The resultant critical stresses.

3. The equipment is essentially satisfactory for proceeding with future testing.

4. The grooved bar should be used for buckling tests.

5. The stress distribution at the edge of the plate is not extremely critical for buckling tests.

6. The buckling and ultimate strength of wide thin plates is not a function of the maximum measured unfairness alone since the initial contour and past history of the plate may have overriding effects.

7. Due to the difficulty of keeping initial deflections small with respect to the thickness for these plates, buckling loads cannot be obtained directly but must be obtained by extrapolating the data.

8. Wide thin plates act like columns and their strength is affected but little by the presence of support at the unloaded edges.

9. Contingent upon the previous conclusions, valuable buckling data was obtained for one series of plates.

10. The theory as presented in Bleich [8] is supported, and can be used at least to predict the approximate critical loads for future experimental works.

11. Insufficient data was taken in the vicinity of the critical load.

12. Insufficient data was obtained to analyze the growth of unfairness in the plates.

13. While no conclusive evidence exists, there is reasonable doubt as to the accuracy of calibration of the testing machine.

## VI. RECOMMENDATIONS

1. Further investigation of the stress distribution should be made, and attempts made to improve it if necessary, using a plate with a larger thickness and smaller a/t ratio. Strains should be measured at one edge (as before), at the center line, and in detail between two adjacent jacks both at the edge and the centerline to determine more completely the nature of the distribution.
2. Further tests should be conducted to compare the operation of the apparatus when the hydraulic jacks are used and when the loading bar bears directly upon the I-beam.
3. Column tests should be run (no "a"-edge supports) to determine whether simple support is obtained at the "b" edge.
4. The test plates will be more accurately cut if sandblasting is done before the edges are machined instead of after.
5. Bleich's theory should be utilized to predict the critical load for future experimental work.
6. More data should be obtained in the region of the critical load.
7. A dial gage with a longer travel is necessary to measure the growth of unfairness as the plate is loaded.
8. Before more tests are made, the testing machine should be calibrated.

# VII. APPENDIX

## A. SUPPLEMENTARY INTRODUCTION

### 1. S-9 Project

Presented herein is a pertinent excerpt of Project S-9 of the Hull Structures Committee of the Society of Naval Architects and Marine Engineers.

Proposal

Project S-9, Buckling Strength of Hull Structures

9 April 1953

"It is the opinion of the S-9 panel that progress in the subject of the buckling strength of hull structures may best be accomplished by a combination of library and experimental research preferably carried out together to avoid duplication and, at the same time, to avoid undue delay. The two proposals presented at the 5 December meeting of the Hull Structure Committee possessed this balance. Since the funds made available do not permit carrying out the dual program proposed, a more modest one based on the same considerations is submitted at this time.

The desired area of study concerns the behavior of elemental flat plates under pure compressive loading. Even for such geometrically simple elements and loadings there is almost no known experimental verification of theory in the range characteristic of transversely framed ship proportions. Witness to this fact is borne out by the extensive use made of Montgomerie's formulations presented before the Society of Naval Architects of Japan in 1934, which nevertheless do not approximate ship conditions in that the short unloaded edges of the plates were unsupported. Furthermore, in this range any data distinguishing between buckling and ultimate loads is almost non-existent.

The concrete proposal here made is to obtain experimental data for flat plates simply supported on all four edges and subsequently for loaded edges elastically supported with unloaded edges simply supported for side ratios (a/b) of .33, .50, .75 and width-thickness ratios (b/t) of 40, 70 and 100. Elastic edge restraint coefficients of .25 and .50 per page 436 of Bleich's "Buckling Strength of Metal Structures," are contemplated for elastic cases.

Following a thorough literature search of this restricted area of the buckling field, such tests might readily be performed on plates 1/8" thick by 3 ft. wide (about 1/4 full size)."

/s/ J. Harvey Evans
Chairman
Panel for Project S-9

## 2. Buckling Theory

The fundamental general equation for a thin flat plate under the action of forces in its middle plane, when the deflection w is small compared to the thickness t, has been developed by St. Venant from a strain energy analysis approach.

$$\frac{EI}{1-\nu^2}\left(\frac{\partial^4 w}{\partial x^4} + 2\frac{\partial^4 w}{\partial x^2 \partial y^2} + \frac{\partial^4 w}{\partial y^4}\right) + t\left(\sigma_x \frac{\partial^2 w}{\partial x^2} + \sigma_y \frac{\partial^2 w}{\partial y^2} + 2\tau_{xy}\frac{\partial^2 w}{\partial x \partial y}\right) = 0 \qquad (1)$$

where $\sigma_x$ and $\sigma_y$ are the normal stresses in the x and y directions and $\tau_{xy}$ is the shear stress. The moment of inertia of a unit strip of plating is $I = \frac{t^3}{12}$, E is Young's modulus, and $\nu$ is Poisson's ratio.

When $\sigma_y, \tau_{xy} = 0$, the equation simplifies to the form,

$$\frac{EI}{1-\nu^2}\left(\frac{\partial^4 w}{\partial x^4} + 2\frac{\partial^4 w}{\partial x^2 \partial y^2} + \frac{\partial^4 w}{\partial y^4}\right) + \sigma_x t \frac{\partial^2 w}{\partial x^2} = 0 \qquad (2)$$

Bleich [8] has suggested an empirical modification of equation (2) for all cases, even those where the critical stress may exclude the proportional limit.

$$D\left(\tau \frac{\partial^4 w}{\partial x^4} + 2\sqrt{\tau}\frac{\partial^4 w}{\partial x^2 \partial y^2} + \frac{\partial^4 w}{\partial y^4}\right) + \sigma_x t \frac{\partial^2 w}{\partial x^2} = 0 \qquad (3)$$

$$D\left(\frac{9\times 2}{9w^{-}}+2\frac{1}{L}\frac{9\times 9d_{2}}{9w^{-}}+\frac{9d^{2}}{9w^{-}}\right)+Q\times\frac{9\times 2}{9c^{-}}=0 \qquad (3)$$

$$\frac{EI}{1-\beta_{2}}\left(\frac{9\times 4}{9w^{-}}+2\frac{9\times 9d_{2}}{9w^{-}}+\frac{9d^{4}}{9w^{-}}\right)+Q\times\frac{9\times 2}{9c^{-}}=0 \qquad (2)$$

Using $c^{-2}\omega^{2}=k^{2}$ the equation simplifies to the form,

placing $\alpha=\frac{\Pi}{k}$ in Hencky's solution, and $\bar{w}$ is obtained's value.

$w^{*}$ in the above manner. The maximum deflection of a unit width of

where $c^{-1}$ and $\delta^{-1}$ are the general theorem in the $\bar{E}$ and $\bar{\Sigma}$ directions and

$$\Sigma\,\omega^{2}\frac{9\times 9d^{2}}{9c^{-}}=0 \qquad (1)$$

$$\frac{EI}{1-\beta_{2}}\left(\frac{9\times 4}{9w^{-}}+2\frac{9\times 9d_{2}}{9w^{-}}+\frac{9d^{4}}{9w^{-}}\right)+\frac{1}{4}\left(\Gamma\frac{9\times 9c^{-}}{9w^{-}}+Q\frac{9d^{-}}{9w^{-}}+\right.$$

## 5. Buckling Theory

The Fundamental governing equations for a thin flat plate under the action of forces in its middle plane, using the deflections $\xi$ as usual, developed by the Galerkin's $\beta$. Just been developed by him. Hencky then a obtain energy principle equations.

Thesis [1] has suggested an empirical modification of equation (2) for all cases, when there exists the artificial stress due inelastic the inelastic limit.

For wide plates, however, he recommends the use of a simplified equation by Ros and Eichinger,

$$D\tau\left(\frac{\partial^4 w}{\partial x^4} + 2\frac{\partial^4 w}{\partial x^2 \partial y^2} + \frac{\partial^4 w}{\partial y^4}\right) + \sigma_x t \frac{\partial^2 w}{\partial x^2} = 0 \qquad (4)$$

since it presents an easier solution, and since the difference between the results of equations (3) and (4) is not very great for such plates.

The general solution of equation (4) is

$$w = \sin \frac{\pi y}{b}\left(c_1 \cos \mathcal{R}_1 \frac{x}{b} + c_2 \cos \mathcal{R}_2 \frac{x}{b}\right) \qquad (5)$$

where $$\mathcal{R}_{1,2} = \frac{\pi}{2}\left(\sqrt{K} \pm \sqrt{K-4}\right)$$

and it develops that when the boundary conditions of simple support are satisfied, the following characteristic equation is obtained:

$$\mathcal{R}_1 \tan \frac{\alpha \mathcal{R}_1}{2} - \mathcal{R}_2 \tan \frac{\alpha \mathcal{R}_2}{2} + \alpha \beta \left(\mathcal{R}_1^2 - \mathcal{R}_2^2\right) = 0 \qquad (6)$$

where $\beta$ is the coefficient of edge restraint.

This equation yields characteristic values of $\sigma_x$ at which the plate changes from one configuration to another, the lowest value being the buckling stress, $\sigma_{cr}$.

$$\sigma_{cr} = \frac{\pi^2 E \tau}{12(1-\nu^2)}\left(\frac{t}{b}\right)^2 K \qquad (7)$$

or $$\sigma_{cr} = \frac{\pi^2 E \tau}{12(1-\nu^2)}\left(\frac{t}{a}\right)^2 \bar{K} \qquad (8)$$

where $$\bar{K} = \alpha^2 K.$$

Bleich presents a table of $\bar{K}$ values for various combinations of and $f$ [Ref. 8, p. 436]. For plates simply supported .

Solution of equation (3) for conditions of simple support at all four edges gives the result

$$\sigma_{cr} = \frac{\pi^2 E \sqrt{\tau}}{12(1-\mu^2)} \left(\frac{t}{b}\right)^2 \left(\frac{\alpha}{n\sqrt[4]{\tau}} + \frac{n\sqrt[4]{\tau}}{\alpha}\right)^2 \qquad (9)$$

where $n$ is the number of half-waves in the buckled shape.

## 3. Determination of Buckling Load

The theoretical buckling load is the load at which the plate suddenly departs from its plane condition and assumes a buckled shape with two-dimensional curvature. This load can be calculated by applying the "least work" approach introduced by Kirchhoff and applied to plates by Bryan. In practice this phenomenon may not occur abruptly due either to initial "unplaneness" of the plate, or to the fact that the yield point is reached in the fibers of the plate before buckling occurs. The buckling load as obtained in practice must be a rather fictitious value found by some less direct means. Methods available are the "top-of-the-knee" method, the "stress-reversal" method, Vasta's method [19], Yoshiki's method 60 , and Southwell's or Donnell's method [48],[18]. The top-of-the-knee method depends upon the rate of change of the lateral deflection with increasing load. This deflection may be measured directly, or the bending moment in the plate as determined by the difference of the strains on opposite sides of the plate may be used as an indicative value. The strain reversal method defines the buckling load as that at which the slope of the strain-load curve for either side

of the plate reverses direction. Vasta's method is based upon the shortening of the plate in the direction of the load, and could be applied with difficulty in this investigation since it is based upon a "constant-deflection" application of the load. Yoshiki attempted to accentuate the change of slope in the load-deflection curve used in the "top-of-the-knee" method by plotting deflection-squared versus the load.

Southwell's method is based upon the bending of a column which has some initial unfairness. Starting with the basic differential equation, the following expression can be arrived at:

$$\frac{d}{P} = \frac{1}{P_{cr}} - \frac{d_o}{P} \qquad (10)$$

If a plot is made of $\frac{d}{P}$ vs. d , the slope of the line is the inverse of the critical load, and the intercept on the d-axis is the initial deflection $d_o$.

Donnell has devised a variation on Southwell's method which has some advantages. If P is plotted against $\frac{P}{d}$ , a line is obtained whose equation is:

$$P = P_{cr} - d_o \frac{P}{d} \qquad (11)$$

The intercept on the P-axis is the buckling load, and the slope is the initial unfairness.

## B. DETAILS OF PROCEDURE

### 1. Design of the Test Apparatus

a) General

The survey of the pertinent literature indicated that Polyclrone [40] and Capozzoli [12] had tested plates of high aspect ratios at Massachusetts Institute of Technology. Equipment was designed and built to provide simple support of the unloaded edges. This equipment was made available to this project if its use proved feasible. The total length of support for each edge was 34"; hence this limited the total length of "a"-edges of each group of plates to be tested if these supports were to be used. A chart was made of the ratios a/b, a/t and "t" of the plate specimens using values of "t" for standard plate sizes and limiting the thickness to 5/16", the maximum capacity of the supports.

The maximum capacity of the materials laboratory hydraulic testing machines was 300,000 pounds. This placed an upper limit on the size of plates which could be tested.

With these two criteria, i.e., the total length of "a"-edges and the testing machine capacity, the plate sizes were selected and are presented in Table I.

b) B-Edges

Since the longest selected plate was 56.75" in length, the testing jig must be about 5 feet in length. The upper head of the testing machine presented an annular bearing surface 18" O.D. by 11" I.D. The lower head was a 2 foot square. Expected load analyses of the proposed plate sizes indicated that size 43.75" x 10.19" x 7/32"

imposed the severest condition on the jig both strength-wise and from the standpoint of distributing the edge loading.

Preliminary calculations indicated that allowing a stress variation of 5% along the loaded edge an I-beam of approximately 12 feet in depth would be required to bridge the gap from the head of the testing machine to 43.75" length of plate edge. This was in line with the experience of the David Taylor Model Basin where constant displacement heads of the same order of magnitude were found necessary.

It was felt that a more practical solution would involve the use of hydraulic means to distribute the load. Accordingly it was found that commercial 20-ton hydraulic jacks could be fitted in the testing jig, seven on each edge connected to a common manifold, which when backed by an I-beam of approximately 18" depth should provide a solution to the problem. These jacks could be placed along the I-beam (See Fig. 27) with different intervals to suit the particular plate size. It was found that these commercial jacks (See Fig. 31) could normally be expected to withstand a 10% overload. Considering this, seven 20-ton jacks would equal the rated capacity of the testing machine, i.e., 300,000 pounds.

There still remained the problem of converting the load from each jack to a more uniform load on the plate edges and still maintaining this edge as simply supported. Frankland [19] merely butted the square edge of the plate against the flat loading lead relying on friction to prevent lateral motion; Yoshiki [60] used the same arrangement except that he rounded the edges of the plate to minimize the rotational restraint.

Since both of these methods necessitated very careful machining of the plate edges, it was felt that the same result could be accomplished by using the milled or slotted cylinders which would fit over the edge of its plate and bear on a loading bar which could also be used to bridge the gap between the jacks. (See Fig. 27) The cylinders, or loading segments should be restricted in length to minimize torsional restraint on the loaded plate edge. Both the segments and the bar could then be hardened to resist deformation under the high loading at the point of contact. The loading bar was ground flat on one surface and flat with a shallow groove in the other surface. It was believed this groove might be necessary to restrict lateral movement of the plate.

c) "A"-Edges

In order to avoid transmittal of load to the "a"-edge supports, these supports should be completely independent and mounted free from the "b"-edge loading arrangement. The "a"-edge support should prevent lateral motion of the edge of the plate while permitting both rotation and translation in the plane of the plate.

It was found that the "a"-edge supports designed by Polychrome [40] and modified by Caporzoli [12] permitted freedom of rotation of the plate edge for about 20° on either side of the plate axis if the ball bearing races were permitted to slide on the channel sides (See Fig. 29). The ball bearing support allows translation in the plane of the plate and can be adjusted to the thickness of the plate by the use of spacers between the race support and the channel, with the final adjustment of the desired pressure being accomplished with the thumb screws. The channels are held in place by an arrangement of

rods and turnbuckles connected to angle iron braces rigidly attached to the frame of the testing machine. (See Fig. 33)

The two "a"-edges are connected to each other by an angle on either side of the plate to prevent the support from slipping off the plate edge. These angles both have one edge planed to serve as a base for the sliding dial gage with which actual deflection measurements ($\delta'$) can be read.

d) Hydraulic Jacks

The I-beams were both skin-machined to provide a flat base for the hydraulic jacks. These jacks are further held in position by two angles on either side which are bolted to the I-beam but hold the jacks only by clamping friction. These angles are slotted to accommodate the hydraulic fittings as the jack positions are changed. The Blackhawk Company, manufacturers of the hydraulic jacks, indicated that reasonably equal pressures could be expected in each jack when several were connected to a common manifold. Some slight variation in delivered force, however, may be expected from varying friction loads in the different jacks and varying back pressures created by the tension in the spring of the piston return mechanism.

Each of the seven jacks along one edge of the plate was connected to a manifold manufactured from 3" diameter cold rolled steel. (See Fig. 30). This manifold also had outlets on which a pump and pressure gage could be mounted. (See Fig. 34).

2. Procedure for Setting Up Equipment

In order to facilitate future use of the equipment a brief description of the method of assembling the test equipment is given. The weight handling equipment consists of a chain hoist and a narrow four wheeled truck which will fit easily between the frame of the testing machine. The steps are as follows:

a.) With the chain hoist and sling place the upper I-beam on the truck and move into position in the testing machine under the upper head of the machine. A 1/4" shim will be found between a spacing ring clamped to the I-beam and the beam itself. This shim should be towards the window. It is convenient to lift the wheels of the truck over the ledge created by the difference in height of the floor level and the lower head, by means of a lever. The wheels are then blocked up to the proper height and the truck moved on to the lower head. Once the equipment is on the lower head it is advisable to raise the lower head slightly, about 1/2" to prevent the possibility of locking equipment between the upper and lower heads. Should such a lock become positive it might be necessary to dismantle the testing machine to remove the equipment.

b.) The upper head is lowered carefully over the 2" stud protruding from the I-beam. The plate washer and nut is secured loosely on the stud. The I-beam may now be lifted clear of the truck and the truck removed. It may be convenient now to lower its I-beam until it barely rests on the lower head. The beam may now be positioned on the head. Scribe marks will be found on the spacing ring and the upper head of the testing machine to facilitate alignment. When the beam is in place the 2" nut should be tightened and the upper head raised about 2 ft. clear of the lower head.

c.) The upper system of jacks, already positioned as desired between the clamping angles may now be lifted as a unit and placed on the truck. It will be found that if care is taken, the jack feet are wide enough to prevent this assembly from tipping. The truck is then moved into position under the upper I-beam and the bolts secured. The upper head and jack system is lifted to a maximum height and the truck removed.

d.) It is usually convenient to leave the lower system of jacks attached to the lower I-beam. This whole assembly then may be lifted on the truck and moved into position on the lower head with only the front wheels on the lower head. The lower head is raised about 1" or 2" and a block is placed under the higher end of the beam. The head is then lowered so that one end of the I-beam now rests on the block. The other end of the beam is then lifted clear of the truck with the chain hoist and the truck removed. The lower head is then raised until the I-beam is nearly supported by it. A 1/4" shim is inserted under the edge of the I-beam nearest the window. It is advisable at this point to position the lower I-beam on the head by lowering the upper head and matching the opposing jacks. Such shims as deemed necessary under the lower head are best inserted at this point. The blocks and chain hoist are then removed and the lower head brought down to about 1" from its lowest position.

e.) The "a"-edge supporting angles with rods attached may then be placed and clamped to the proper height on the H-beam frames of the testing machine. The "a"-edge channels, held together with their supporting angles which are spaced according to the width of the plate specimen, are slid into position and rested on the ends of the lower loading bar. The turnbuckles may then be secured and the "a"-edge supports lined up.

f.) After initial deflection of the plate readings are taken, the test plate is placed in position between its "a"-edge channels and rested on the lower loading bar. The ball-bearing races are inserted to hold the plate in place. The shims for the loading segments, if used, are held in position along the top edge either with C-clamps or a segment placed at each end, or both. The gasket material may be placed along the edge and the remaining segments positioned on the top edge of the plate over the gasket and shims. The method of placing the segments along the bottom edge of the plate depends upon the type of gasket material used. The thumbscrews on the "a"-edge channels are tightened so that the plate may be suspended from the "a"-edge supports. The lower head of the testing machine is then lowered slightly. If solder gasket material is used, the head is lowered about 1/2". The segments may then be slid into position from either end of the plate. The solder may also be run in from the end of the plate between the segments and the plate edge. The shims are then inserted between the segment and the side of the plate. If a flat gasket such as the neoprene strip is used the segments must be rolled in from the side of the plate. Careful spacing of the distance between the plate edge and the loading bar is necessary to accomplish this successfully. The lower head is then raised until the plate is supported. Both upper and lower head and the "a"-edge supports are then positioned so that approximately equal plate overhang remains above and below each "a"-edge support. The plate is now ready to load.

g.) The strain gage hook up may now be completed and zero readings taken. The pressure gage and hand pump may be connected to the manifolds if desired. A slight load should be placed on the plate, probably not exceeding 1000 pounds. The loaded edges of the plate may be forced into

a straight line as the segments tend to seek the lowest part of the groove in both loading bars. It is useful to apply some grease to the loading bar grooves to facilitate this operation and subsequent sliding when plate deflections are large. The straightness of the edge may be checked by eye or with a straight edge. Zero or near-zero deflection readings may be taken with the dial gage at desired locations along the horizontal center line of the plate.

h.) The application of the load should be gradual at first until all jacks have time to equalize their internal pressure. There should be about 2" of each jack ram protruding, more perhaps when higher loads are reached. The amount will depend on the degree of leakage in the system. A stress of about 1000 psi is needed to deform the solder gasket if this type is used. The load corresponding to this stress should be placed on the plate and allowed to remain until the rate of decrease of its load is nearly zero. If it is desired to obtain test points below this loading care must be taken not to unload the plate entirely if straightening of the "b"-edge was required. The test is now ready to proceed.

i.) Disassembly of the equipment generally follows the reverse of the method described above.

## 3. Explanation of Test Description

In order to evaluate the effect of the various components of the test apparatus, tests under different conditions were run and described cryptically in the data sheets and on the graphic results. (Figs. 1 to 20).

a.) Load Application - Machine or Pump

It was intended that each set of hydraulic jacks (top and bottom) would be connected to a common manifold with the jacks partially extended. The testing machine would then be used to apply the load to the jack system. In an attempt to evaluate effects of jack friction a hydraulic hand pump was connected to the top group of jacks and the load was applied in this manner. It was found also that the quieter operation of the hand pump was more conducive to efficient test procedure, hence this method was generally used on subsequent tests.

b.) Jacks - No Jacks

One set of tests was run without the hydraulic jacks in order to ascertain their effect. When the jacks were removed the two loading I-beams were shimmed so as to be as nearly parallel as practicable.

c.) Bar

The hardened loading bar designed for the apparatus is designated by the thickness (3/4") and whether the flat (F) or grooved (G) side of the bar bore on the segments. (See detail Fig. 27). Since the loading pressures on this particular size of plate are comparatively low, cold rolled steel bars 1 1/4" wide and thicknesses 1/16", 1/4", 5/16" and 3/8" were substituted in various tests in an effort to shed light on the effect of the stiffness of the bar on the test results.

d.) Gasket

In an attempt to eliminate local unevennesses in the edge of the test plate various sizes and types of gasket materials were placed along the edge of the plate under the bearing segments. Where a plastic gasket material was used such as the solder, the gasket was first set by running up the load to approximately 20,000 pounds and allowing the gasket material

to flow plastically for several minutes until the rate of drop in the load was approximately equal to that of normal leakage in the hydraulic system.

The neoprene gasket was cut from a sheet 1/16" thick to a width equal to the approximate thickness of the test plate. Two diameters of solder gaskets were used, 1/16" and 3/32". The 1/16" solder was used as a double strip side by side, whereas only a single strip of the 3/32" diameter solder was used. During two tests where no segments were used, a strip of lead house sheathing about 1" wide and 1/16" thick was placed between the loading bar and the edge of the plate.

e.) Segments - No Segments

Since most of the test results indicated the presence of fairly high moments in the plate from the beginning of the tests, it was decided advisable to determine whether or not the bearing segments influenced this phenomenon. Accordingly during several tests these segments were removed and the plate was butted up against a sheet lead gasket on the loading bar.

f.) Shims - No Shims

The segments were made with the slot a minimum of 1/32" wider than the plate. In order to reduce the possibility of eccentric loading and to check the effect of this clearance on the observed moments in the test plate shim stock was inserted to reduce this clearance. On the tests where shims are indicated, shim stock of .015" and .002" were placed between both sides of the segment and the plate making a total addition of shim stock .034" on each "b"-edge. The maximum estimated clearance between the plate and the segments after the introduction of these shims is .003".

g.) Load

The load was measured on the most sensitive gage of the testing machine that would record the load. Three gages are available of ranges 0-30,000 pounds, 0-150,000 pounds, 0-300,000 pounds. All gages have adjustable zero readings so that the weight of the apparatus in the machine is compensated except for the upper loading bar and segments.

h.) Pi - Internal Hydraulic Pressure of Top System of Jacks

In order to provide a check on the total load recorded in the testing machine and to aid in determining the force system on the loading bar should this be necessary, a pressure gage 0-1000 pounds was mounted directly on the upper manifold of the top hydraulic jack system and the pressures recorded.

i.) Strain Gage Readings

These readings are direct readings of the strain gage indicator. The index number did not change during any given test and to save space this number is recorded only under the zero reading. The zero reading was taken after the gasket had been set but with the blocks used to minimize the curvature of the test plate in the "b"-edge direction, still in place. Time did not permit complete cycling of the gages on each run but final zero readings were taken periodically to check the instrumentation. The dummy gage was mounted on a plate of the same thickness and same material as the test plate. The leads to the strain gage indicator were about the same length as those from the test plate. The dummy gage was located as close as practicable to the test plate.

j.) Deflections

Initial deflections in the "a"-edge direction were recorded on

Plates 2, 3, and 4 at 6" intervals from the center line and at the center. Deflections at the center line in the "b"-edge direction were recorded at each gage location on Plates No. 1 and No. 2 except near the "a"-edges on Plate No. 1 where wiring interfered. Here the deflection noted was between the two end gages as noted. Deflections on Plate Nos. 3 and 4 were recorded at the same location as the initial readings. It will be noted that in certain cases the deflections exceeded the maximum travel of one-half inch on the dial gage.

k.) Plate Orientation

In Figs. 1 to 20 the plate orientation is indicated by the number of the strain gage in each corner. This plate was reversed during later tests along a diagonal as a check on effect of unevenesses in the edge of the plate.

l.) Computed Strain

The computed average strain based on a load of 10,000 pounds and the area of the test plate (b' x t) assuming a value of E 28,300 kips/inch$^2$ is shown as a dashed horizontal line

$$\sigma_{av} = \frac{10\,000}{56.75 \times .15625 \times 28.3 \times 10^6} = 40.3\ \mu\text{in/in}$$

Since the accuracy of the individual strains plotted is $5\ \mu$in/in only values of the individual strains above 45.3 or below 35.3 should be considered as different from average values.

4. Data on Test Plates

a.) Length - L = 13.3125"

b.) Width - b' = 56.75"

c.) Thickness - This dimension varied slightly among the four test plates. Measurements were taken along the edge with a micrometer. The

plates were weighed and an average thickness determined assuming a density of steel 0.283 pounds/inches$^3$. The surface of the plates were slightly pitted from corrosion and shot blasting. The depth of pits was determined fairly accurately by measuring the "a"-edge where the surface had been ground to the depth of the pits. An average depth of pits as determined by this method is 0.002". The pitting is fairly evenly distributed over the surface and it is estimated that an average thickness is to one half of the average depth of pits. However the effective thickness of its plates is considered to be the thickness to the bottom of the pits since the lines of stress will not follow the contour of the pits to a marked degree. This same procedure is followed in calculating the value of the modulus of elasticity (E), hence the effect will tend to cancel in the analysis of plate strength.

| Plate No. | Weight (lbs) | $t_{av.}$ $\frac{wgt.}{.283 lb^3}$ (in) | $t_{av.}$ (micr.) (in) | Pits (in) | $t_{av}$ (corrected) (in) |
|---|---|---|---|---|---|
| 1 | 34 | .159 | .1575 | .002 | .1535 |
| 2 | 34.2 | .160 | .1585 | .002 | .1545 |
| 3 | 33.8 | .158 | .1585 | .002 | .1545 |
| 4 | 34.8 | .163 | .1580 | .002 | .1540 |

Nominal thickness of the plate is 0.15625"

Since the scale was accurate to 0.5 pounds and its density of the steel was assumed, it is believed the micrometer readings, even though taken only around the edge of the plate, give a more accurate reading of the plate thickness.

d.) Ratios

"B"-edge Dimension: Defined as the length between "a"-edge supports. 1/4" on each end of the plate was allowed beyond the center line of the

row ball bearings in the "a"-edge support.

$$b = b' - 2 \times 1/4" = 56.25"$$

"A"-edge Dimension: It was considered originally that this dimension should be the over-all width of the plate plus the distance added by inserting the loading segments over the plate edge. The plate sizes were determined on this basis. Further reflection indicated that the true length of the "a"-edge dimension should not include the addition due to the segments. The edge of the plate extends to the center of the segment (minus gasket thickness). The load however is always applied through this center even after deformation since the segment is circular in cross section.

$$a = \text{width of plate} = 13.3125"$$


$$\text{Aspect Ratio} - a/b = \frac{13.3125}{56.25} = 0.237$$

$$\text{Thickness Ratio} - a/t = \frac{13.3125}{t}$$


| | |
|---|---|
| = 85.4 | Plt. # 1 |
| 84.8 | Plt. # 2 |
| 84.8 | Plt. # 3 |
| 85.1 | Plt. # 4 |

FIG.

## DETAILS OF LOADING ARRANGEMENT





ARRANGEMENT OF UPPER HEAD
LOWER HEAD SIMILAR





NOTE: CUT FROM $\frac{3}{4}$" STOCK & HARDENED TO ROCKWELL C-50

"B"-EDGE BEARING BAR
MATL: STL AISI C-1045





JACK FOOT
MATL: MILD STEEL





| .284 MIN. | | .251 MIN. | | .190 MIN. | |
|---|---|---|---|---|---|
| QTY | L | QTY | L | QTY | L |
| 44 | 0.50 | 44 | 0.50 | 44 | 0.50 |
| 44 | 0.875 | 74 | 0.875 | 94 | 0.875 |

"B"-EDGE BEARING SEGMENTS
MATL: $\frac{3}{4}$" DRILL ROD
MILLED & HARDENED TO ROCKWELL C-50




DETAIL OF SEGMENT
WITH SHIMS & GASKET


DETAILS OF LOADING ARRANGEMENT




SECTION B-B

FIG.


DETAILS OF LOADING ARRANGEMENT




DETAIL AT CORNER OF TEST PLATE

DRAWN TO SCALE


1"





CROSSECTION OF "A"-EDGE SUPPORT

5/7/54 MP

# FIG. 30
# DETAILS OF LOADING ARRANGEMENT




MANIFOLD





DEFLECTOMETER

5/16/54 MP

# BLACKHAWK MFG. CO.

MILWAUKEE, WIS.

ENG. DEPT. — R225 & R251 PORTO-POWER RAM SPECIFICATIONS. — OCT. 23, 1941.


10 1/8"
3/8" STD BRIGGS PIPE TAP
1 23/32"
.749" DIA .750"
1 3/4"
3/16"
2" BRIGGS PIPE THRD
2 7/16" DIA
2" BRIGGS PIPE TAP
1 7/16"
2.560" DIA 2.562"
2 1/8" DIA
2.372" DIA 2.375"
3.192" DIA 3.195"
3/16"-12-AM NAT. THRD 3.2544"-3.2584" P. DIA.
FOR 5/16"-24-FIL. HD. SCREW
FLAT OR GAGE TO ENTER 3/8" BELOW SURFACE.
1 1/16"
R225 RAM 10 7/32" COLLAPSED HEIGHT. 15 9/32" EXTENDED HEIGHT.
R251 RAM 11 5/16" COLLAPSED HEIGHT 16 3/8" EXTENDED HEIGHT.
1.810" DIA 1.8125"
SADDLE FOR R225 RAM.

R225 RAM WEIGHT 20 1/4 LBS.
R251 RAM WEIGHT 21 1/2 LBS.
RATED CAPACITY 20 TON.
RAM DIA. 2.562"
RAM TRAVEL 5.062"
RAM AREA 5.1572 SQ. IN.
OIL CAPACITY 26.1 CU. IN.

163 STROKES FOR TOTAL TRAVEL OF 5.062"
.031 INCH PER STROKE OF P76 PUMP.
INTERNAL PRESSURE AT RATED CAPACITY OF 7750 LBS. PER SQ. INCH.
HANDLE EFFORT ON PUMP 89 LBS.

USE WITH P76 PUMP.

SHEET 74

FIGURE NO. 32

TEST APPARATUS





FIGURE NO. 33

TEST APPARATUS



## C. Summary of Data and Calculations

### Table III A

### Evaluation Tests

P = 20,000 lb. $\varepsilon_{av}$ = 81.1 in./in.

| Test No. | * | $\varepsilon$ av | Lowest $\varepsilon_a$ | % under | Highest $\varepsilon_a$ | % over | Max. % |
|---|---|---|---|---|---|---|---|
| 1 | T | 85.5 | 46.5 | 42.7 | 153.0 | 88.6 | 88.6 |
| | B | 78.0 | 35.0 | 56.9 | 152.0 | 87.5 | |
| 4 | T | 82.2 | 48.0 | 40.8 | 126.5 | 56.0 | 56.0 |
| | B | 69.7 | 39.5 | 51.4 | 94.5 | 16.6 | |
| 5 | T | 76.9 | 51.5 | 36.6 | 94.5 | 16.6 | 43.9 |
| | B | 70.1 | 45.5 | 43.9 | 102 | 25.8 | |
| 6 | T | 76.1 | 48 | 40.8 | 110.5 | 36.3 | 40.8 |
| | B | 69.0 | 47.5 | 41.5 | 96.5 | 19.0 | |
| 7 | T | 69.8 | 34.5 | 57.5 | 97.0 | 19.6 | 71.0 |
| | B | 71.2 | 23.5 | 71.0 | 105.0 | 29.5 | |
| 13 | T | 81.7 | 55.5 | 31.6 | 111 | 36.9 | 49.3 |
| | B | 78.1 | 47.0 | 42.1 | 121 | 49.3 | |
| 14 | T | 78.0 | 47.0 | 42.1 | 138.5 | 70.8 | 70.8 |
| | B | 72.6 | 52 | 35.9 | 95.5 | 17.8 | |
| 15 | T | 66.1 | 22 | 73.0 | 118.5 | 46.2 | 74.8 |
| | B | 62.7 | 20.5 | 74.8 | 88.0 | 8.5 | |
| 16 | T | 72.0 | 52.5 | 35.3 | 145.5 | 79.4 | 79.4 |
| | B | 72.4 | 26 | 68.0 | 112.5 | 38.8 | |
| 17 | T | 69.3 | 35 | 56.9 | 118.5 | 46.2 | 81.5 |
| | B | 64.1 | 15 | 81.5 | 120.5 | 48.6 | |
| 18 | T | 70.9 | 29 | 64.3 | 106 | 30.7 | 79.1 |
| | B | 70.2 | 17 | 79.1 | 112.5 | 38.8 | |

* T = Top of plate ; B = Bottom of plate

## 5. Summary of Data and Calculations

Table XIX A

Production Tests

P = 80,000 lbs. $\varepsilon_{av}$ = 82.4 Yds.

| Test No. | * | $\varepsilon_{av}$ | Lowest $\varepsilon_a$ | $\beta$ value | Highest $\varepsilon_a$ | % over | Yds. $\varepsilon$ |
|---|---|---|---|---|---|---|---|
| 1 | T | 82.6 | 64.2 | 69.7 | 531.6 | 82.4 | 66.4 |
| | B | 78.6 | 78.0 | 84.9 | 540.2 | 87.6 | |
| 4 | T | 82.1 | 69.0 | 40.8 | 438.5 | 32.0 | 76.2 |
| | B | 84.7 | 72.5 | 52.4 | 74.5 | 14.4 | |
| 5 | T | 74.9 | 82.5 | 36.6 | 74.6 | 24.4 | 43.9 |
| | B | 74.1 | 46.5 | 43.9 | 102 | 42.8 | |
| 6 | T | 76.3 | 48 | 40.6 | 118.1 | 36.3 | 64.4 |
| | B | 69.0 | 47.5 | 41.2 | 96.5 | 18.0 | |
| 7 | T | 64.8 | 74.2 | 57.5 | 87.8 | 18.6 | 72.8 |
| | B | 72.3 | 53.9 | 71.8 | 105.0 | 46.1 | |
| 12 | T | 66.7 | 58.5 | 34.5 | 111 | 34.7 | 49.1 |
| | B | 74.1 | 47.8 | 48.1 | 101 | 43.3 | |
| 14 | T | 74.8 | 41.8 | 46.1 | 134.0 | 70.8 | 74.2 |
| | B | 72.4 | 54 | 45.9 | 78.4 | 12.4 | |
| 15 | T | 66.3 | 52 | 72.8 | 134.3 | 46.6 | 46.2 |
| | B | 62.7 | 80.8 | 74.4 | 88.0 | 8.5 | |
| 16 | T | 72.2 | 72.8 | 36.8 | 116.4 | 72.4 | 79.4 |
| | B | 74.4 | 41 | 68.4 | 132.4 | 36.8 | |
| 17 | T | 48.3 | 34 | 76.9 | 134.4 | 46.2 | 62.3 |
| | B | 64.2 | 15 | 61.3 | 132.2 | 46.6 | |
| 18 | T | 70.8 | 49 | 44.3 | 140 | 30.7 | 72.2 |
| | B | 70.2 | 47 | 74.2 | 112.5 | 34.8 | |

T = Top of plate ; B = Bottom of plate

Table III B

Buckling Tests

| Plate No. | 1 | 2 | 3 | 4 |
|---|---|---|---|---|
| a (in.) | 13.313 | 13.313 | 13.313 | 13.313 |
| b (in.) | 56.75 | 56.75 | 56.75 | 56.75 |
| t (in.) | 0.1535 | 1.545 | 1.545 | 1.540 |
| a/b | 0.237 | 0.237 | 0.237 | 0.237 |
| a/t | 86.8 | 86.2 | 86.2 | 86.5 |
| b/t | 370 | 367 | 367 | 368 |
| $d_0$ (measured) (in.) | 0.085 | 0.057 | 0.009 | 0.071 |
| $d_0$ (Donnell) (in.) | 0.038 | 0.059 | 0.018 | 0.060 |
| $d_0$ (Southwell) (in.) | 0.044 | 0.061 | 0.019 | 0.062 |
| $\sigma$ ult (exp.) (psi) | 4140 | 3375 | 3720 | 3830 |
| $\sigma$ cr (Theory) (psi) | 3780 | 3830 | 3830 | 3810 |
| $\sigma$ cr ("T.O.K.") (psi) | 3730 | 2620 | 3210 | 3190 |
| $\sigma$ cr (Donnell) (psi) | 4640 | 3530 | 3580 | 4120 |
| $\sigma$ cr (Southwell) (psi) | 4520 | 3540 | 3635 | 3940 |
| $\frac{\text{Donnell - Bleich}}{\text{Bleich}} \times 100$ | + 23.4 | -7.83 | -6.53 | + 7.61 |

## Section III B

### Modelling Theory

| Plate No. | 1 | 2 | 3 | 4 |
|---|---|---|---|---|
| a (in.) | 13.313 | 13.113 | 13.313 | 13.313 |
| b (in.) | 56.75 | 56.75 | 56.75 | 56.75 |
| h (in.) | 0.1250 | 1.250 | 1.250 | 1.250 |
| a/b | 0.237 | 0.237 | 0.237 | 0.237 |
| b/h | 64.4 | 64.4 | 64.4 | 64.4 |
| b/h | 345 | 345 | 345 | 345 |
| $d_x$ (inches) | 0.000 | 0.027 | 0.000 | 0.000 |
| $d_y$ (inches) | 0.000 | 0.019 | 0.000 | 0.000 |
| $d_z$ (inches) | 0.000 | 0.041 | 0.000 | 0.000 |
| $\sigma_x$ (psi) | 1110 | 1110 | 1110 | 1110 |
| $\sigma_y$ (psi) | 1110 | 1110 | 1110 | 1110 |
| $\sigma_z$ (psi) | 1110 | 1110 | 1110 | 1110 |
| $\sigma_{xy}$ (psi) | 1110 | 1110 | 1110 | 1110 |
| $\sigma_{yz}$ (psi) | 1110 | 1110 | 1110 | 1110 |
| $\sigma_{zx}$ (psi) | 1110 | 1110 | 1110 | 1110 |

$$\text{Poisson's Ratio} = \frac{\text{Ratio} \times 100}{\text{Reduction}}$$

## D. SAMPLE CALCULATIONS

1. The longitudinal strain in the plate at a given point on its neutral axis was obtained by averaging the strains obtained from a pair of gages mounted on opposite sides of the plate and opposite each other as shown on Fig. 15. All odd numbered gages were on one side of the plate, and all even numbered gages were on the other, the arrangement being such that each odd gage had opposite it the gage with the next highest even number.

$$\varepsilon_a = \frac{\varepsilon_1 + \varepsilon_2}{2}$$

Thus for gage numbers 67 and 68 in Test No. 19 on Plate No. 1, at a load of 20,000 pounds,

$\varepsilon_1 = +181$ microinches/inch

$\varepsilon_2 = -359$ microinches/inch

$$\varepsilon_a = \frac{(+181) + (-359)}{2} = -89 \text{ microinches/inch}$$

2. The average longitudinal stress in the plate was obtained by dividing the total applied load by the edge area of the plate.

$$\sigma_{av} = \frac{P}{b' \times t}$$

For Test No. 19 on Plate No. 1 at a load of 20,000 pounds,

$P = 20{,}000$ lbs.

$b' = 56.75$ in.

$t = 0.1535$ in.

$$\sigma_{av} = \frac{20{,}000}{(56.75)(0.1535)} = 2295 \text{ psi}$$

For the same test, at the critical load,

$P_{cr} = 40{,}400$ lbs. (Donnell)

$$\sigma_{av} = \frac{40{,}400}{(56.75)(0.1535)} = 4640 \text{ psi}$$

## 8. Bending Stresses in Plates

1. The longitudinal stresses in the plate at a given point on the neutral axis was obtained by computing the stresses obtained from a pair of simple beams as explained in either of the plate and cylinder methods as given on Pg. 117. All combined plates were in one side of the plates, and all even numbered plates were on the plates. The corresponding bending moment which must only take but opposite if the plate with the most highest moment.

$$\frac{E_x}{3} = \frac{E_y}{3}$$

Thus for plate number 67 and 68 in Plate No. 14 on Plate No. 1, at a load of 80,000 pounds.

$E_y$ = +118 microinches/inch

$E_x$ = -189 microinches/inch

$$E_a = \frac{(+118) + (-189)}{2} = -35 \text{ microinches/inch}$$

2. The average longitudinal stresses in the plate was obtained by dividing the total applied load by the edge area of the plate.

$$C_{av} = \frac{P_t \times s}{b}$$

For Tank No. 14 on Plate No. 1 at a load of 80,000 pounds,

$P$ = 80,000 lbs.

$P_t$ = 80.00 lbs.

$t$ = 0.1339 in.

$$C_{av} = \frac{(24 \times 80)(0.1339)}{80,000} = .0032 \text{ psi}$$

For the same tank, at the outlined hole,

$P_{ca}$ = 10,500 lbs. (measured)

$$C_{av} = \frac{10,500}{\pi(3)} = 1110 \text{ psi}$$

3. Average strain was calculated using the stresses obtained above and the value of E obtained from Appendix F.

$$\varepsilon_{av} = \frac{\sigma_{av}}{E}$$

$E$ = 28,300,000 psi

At 20,000 pounds,

$$\varepsilon_{av} = \frac{2295}{28,300,000} = 81.1 \text{ microinches/inch}$$

A different value for $\varepsilon_{av}$ is obtained if the plot of axial strain ($\varepsilon_a$) is integrated by the trapezoidal rule along the line of gages, numbers 7, 8 through 35, 36. (A value of 81.1 will be assumed for the axial strain at gages 35 and 36, since no readings were obtained at these gages for this test.)

$$\varepsilon_{av} = \frac{1}{14}\left[\frac{1}{2}\varepsilon_{a(7,8)} + \sum_{(9,10)}^{(33,34)} \varepsilon_a + \frac{1}{2}\varepsilon_{a(35,36)}\right]$$

$$\varepsilon_{av} = \frac{1}{14}(1046.6) = 74.8 \text{ microinches/inch}$$

4. Percentage of maximum deviation of axial strain from average strain as computed from the total load.

$$\% = \frac{\varepsilon_a - \varepsilon_{av}}{\varepsilon_{av}} \times 100$$

$$\varepsilon_{av} = \frac{P}{E_c t} = 81.1 \text{ microinches/inch}$$

$\varepsilon_a$ max = 116 microinches/inch

$\varepsilon_a$ min = 50 microinches/inch

Max % over = $\frac{116-81.1}{81.1} \times 100$ = 43.0% over

Max % under = $\frac{50-81.1}{81.1} \times 100$ = 38.4% over

5. Discuss effects not mentioned above that would affect the accuracy obtained in the volume of a spherical shell (Problem 3).

5. Strain difference (proportional to lateral deflection) was obtained by subtracting readings of opposite gages. Arbitrarily this was taken as

$$\varepsilon_2 - \varepsilon_1 = \varphi(d)$$

For Test No. 19 on Plate No. 1, using the values in (1) above,

$$\varepsilon_2 - \varepsilon_1 = -359 - (+181) = -540 \text{ microinches/inch}$$

6. Critical load (Top-of-the-Knee Method). To obtain this value no calculations other than those given above for $\sigma_{av}$ and $(\varepsilon_2 - \varepsilon_1)$ were necessary. After plotting $\sigma_{av}$ vs. $(\varepsilon_2 - \varepsilon_1)$ the tangents at the extremities of the curve were drawn. The intersection was taken as the buckling point.

$$\sigma_{cr} = 3730 \text{ psi}$$

7. Critical load (Southwell's Method).

$$\varepsilon_2 - \varepsilon_1 = \varphi(d)$$

$$\frac{\varepsilon_2 - \varepsilon_1}{P} = \frac{\varphi(d)}{\text{Load}}$$

For gages number 67 and 68 in Test No. 19, Plate No. 1 at a load of 20,000 pounds,

$$P = 20{,}000 \text{ lbs.}$$

$$\varepsilon_2 - \varepsilon_1 = -540 \text{ microinches/inch (from above)}$$

$$\frac{\varepsilon_2 - \varepsilon_1}{P} = \frac{540}{20{,}000} = 0.0270$$

A plot of $\frac{\varepsilon_2 - \varepsilon_1}{P}$ - vs. $\varepsilon_2 - \varepsilon_1$ gives a straight line with a slope equal to the critical load.

5. Steps (Continued) (Concentrated to help if understood the original by substituting readings or equals in place. Alternately they can be taken as

$$\frac{E_p - E'}{p} = \frac{E_p - E'}{q} \quad (4)$$

For Test No. 12 on Plate No. 6, using the values in (2) above,

$$E_p - E' = -320 - (+12.1) = -332.1 \text{ volts secondary/cm}$$

6. Original Load (Improved-Procedure Method). To obtain this value no calculations other than those given above for $C_{sc}$ and $(E_p - E')$ were necessary. After plotting $C_{sc}$ vs. $(E_p - E')$ the tangents at the extremities of the curve were drawn. The intersection was taken as the desired point.

$$C_{sc} = 3230 \text{ mf}$$

7. Original Load (Conventional Method).

$$E_p - E' = \frac{p}{q}(4)$$

$$\frac{E_p - E'}{p} = \frac{\text{(4) above}}{q}$$

For Plate number 12 and 13 in Test No. 12, Plate No. 7 at a load of 20,000 pounds,

$$p = 20{,}000 \text{ lbs.}$$

$$E_p - E' = -332.1 \text{ volts secondary/unit (from above)}$$

$$\frac{E_p - E'}{p} = \frac{\text{Eq. (4)}}{20{,}000} = 0.0166$$

A plot of $\frac{E_p - E'}{p}$ vs. $E_p - E'$ gives a straight line with a slope equal to the original load.

$$P_{cr} = \frac{\partial[(\varepsilon_2-\varepsilon_1)]}{\partial[(\varepsilon_2-\varepsilon_1)/P]}$$

$P_{cr}$ = 39,400 lbs.

$$\sigma_{cr} = \frac{P_{cr}}{b'xt} = 4520 \text{ psi}$$

The intercept of the straight line with the $(\varepsilon_2-\varepsilon_1)$ axis represents an equivalent initial deflection of the plate.

$$(\varepsilon_2-\varepsilon_1)_o = 355 \text{ microinches/inch}$$

$$w = d_o \sin \frac{\pi x}{L}$$

$$M_x = -D\frac{\partial^2 w}{\partial x^2} = Dd_o \frac{\pi^2}{L^2} \sin \frac{\pi x}{L}$$

$$M_x = Dd_o \frac{\pi^2}{L^2} \quad \text{when } x = \frac{L}{2}$$

$$\sigma_{max} = \frac{M_x t}{2I} = \frac{E(\varepsilon_2-\varepsilon_1)}{2}$$

$$M_x = \frac{EI(\varepsilon_2-\varepsilon_1)}{t}$$

$$D = \frac{Et^3}{12(1-\nu^2)} = \frac{EI}{1-\nu^2}$$

$$\frac{EI}{1-\nu^2}\frac{\pi^2}{L^2} d_o = \frac{EI(\varepsilon_2-\varepsilon_1)}{t}$$

$$d_o = \frac{(1-\nu^2)\,L^2}{\pi^2 t}(\varepsilon_2-\varepsilon_1)$$

$\nu$ = 0.3

L = 13.313 in.

t = 0.1535 in.

$(\varepsilon_2-\varepsilon_1)$ = $355 \times 10^{-6}$ in./in (from above)

$$d_o = \frac{0.91}{\pi^2}\frac{(13.313)^2}{0.1535}(355 \times 10^{-6}) = 0.0376 \text{ in.}$$

$$P_{cr} = \frac{9[(\varepsilon_2-\varepsilon_1)/\varepsilon]}{9[(\varepsilon_2-\varepsilon_1)]}$$

$$P_{cr} = 10^{\wedge}\text{psi}$$

$$C_{cr} = \frac{P_{cr}}{P_{max}} = \text{from above}$$

The buckling of the plexiglas tube with the $(\varepsilon_2-\varepsilon_1)$ wide transducer
an unplasticized instant deflection of the plate.

$$(\varepsilon_2-\varepsilon_1)^{\wedge} = \text{XIE microinches/inch}$$

$$\sigma = \text{from } \frac{\partial^2 w}{\partial x^2}$$

$$M^{\wedge} = -\text{at } \frac{\partial^2 w}{\partial x^2} = -\text{IN}^{\wedge} \frac{\Gamma_{cr}}{K_{cr}} \text{ at } \frac{L}{2}x$$

$$M^{\wedge} = \text{IN}^{\wedge} \frac{\Gamma_{cr}}{K_{cr}} \text{ where } x=\frac{L}{2}$$

$$C_{max} = \frac{M^{\wedge}c}{I} = \frac{\text{MI}(\varepsilon_2-\varepsilon_1)}{2}$$

$$M^{\wedge} = \frac{4}{\text{MI}(\varepsilon_2-\varepsilon_1)}$$

$$E = \frac{2(1-\nu^2)}{\text{IN}} = \frac{3-\nu}{\text{EI}}$$

$$\frac{\text{EI}}{3-\nu} \frac{K_B}{\lambda} d\phi = \frac{\text{MI}(\varepsilon_2-\varepsilon_1)}{4}$$

$$d\phi = \frac{\lambda}{[\text{IN}-(\nu)]\ K_B} (\varepsilon_2-\varepsilon_1)$$

$$\nu = 0.3$$

$$E = 17.2\text{E}3 \text{ psi}$$

$$t = 0.7525 \text{ in.}$$

$$(\varepsilon_2-\varepsilon_1) = \text{XIE} = \text{IN}_{cr} \text{ in}^{\wedge}/\text{in (from above)}$$

$$d\phi = \frac{\lambda}{\text{EI}} \frac{0.7525}{(17.2\text{E}3)_3} \quad (\text{XIE} = (\text{in}^{\wedge}/\text{in}) \cdot \text{microinch/in.})$$

8. Critical load (Donnell's Method). Donnell's type of plot determines the critical load directly as the intercept on the P-axis of the plot of P vs. $P/(\varepsilon_2 - \varepsilon_1)$.

For Test No. 19, Plate No. 1,

$P_{cr}$ = 40,400 lbs.

$$\sigma_{cr} = \frac{P_{cr}}{b't} = 4640 \text{ psi}$$

The slope of the plot is the equivalent initial deflection

$$(\varepsilon_2 - \varepsilon_1)_o = \frac{\Delta[P]}{\Delta[P/(\varepsilon_2 - \varepsilon_1)]} = 415 \text{ microinches/inch}$$

$d_o$ = 0.0442 in.

9. Theoretical Critical Stress

a. $$\frac{\sigma_{cr}}{\tau} = \frac{\pi^2 E}{12(1-\nu^2)}\left(\frac{t}{a}\right)^2 k$$

E = 28,300,000 lbs/in.$^2$

$\nu$ = 0.3 (assumed)

a = 13.313 in.

b = 56.25 in.

$\frac{a}{b}$ = 0.237

k = 1.113 (Table 40, p. 436)

$\tau$ = 1.000

$\sigma_{cr}$ = 160,400 $t^2$

| Plate No. | t (in.) | $\sigma_{cr}$ (psi) |
|---|---|---|
| 1 | .1535 | 3780 |
| 2 | .1545 | 3830 |
| 3 | .1545 | 3830 |
| 4 | .1540 | 3810 |

| | | |
|---|---|---|
| 7 | 1.7570 | 1.0000 |
| 6 | 1.7570 | 1.0000 |
| 5 | 1.7570 | 1.0000 |
| 4 | 1.7570 | 1.0000 |
| 3 | 1.7572 | 1.0000 |
| Number Nu- | $\ell$ (in-) | $L^{(n)}(\ell_{nu})$ |

$\sigma_{cr}^{(n)} = 2.0 \times 10^{6}$ psi

$\lambda_n = 1.7570$

$\frac{L}{\rho} = 1.7572$ (Simple End Be- ring)

$\frac{L}{\rho} = 0.7121$

$\rho = 1.7570 \times 10^{6}$ in.

$\ell = 1.7570 \times 10^{6}$ in.

$\lambda = 0.12$ (Assumed)

$E = 2.0 \times 10^{6}$ lbs/in$^2$

$\sigma_{cr} = \frac{\lambda^2}{\ell^2} \left(\frac{\ell}{\ell}\right)^2 \frac{\pi^2 E}{12(1-\mu^2)}$

$\sigma^{n} = 0.7570$ in.

5. Dimensionless Critical Stress

$(\ell_n - \ell_1)^n = \frac{q[\lambda/\ell_n - \ell^2]}{q[\lambda^2]} = .722$ approximately

The ratio of the plate is the equivalent reduced thickness.

$\ell_{cr} = \frac{2\pi E}{\lambda_{cr}} = .7570$ psi

$\lambda_{cr} = 10.7/20$ in.

For Case No. 12, State Ref. 2.

2 ans. $\lambda/\ell_n = \ell^2$).

6. Simply Edge Clamped, a Buckled. Determine edge of plate deformation due restrained plate elasticity on the difference in the Poisson ref. plus plate of

b. $\sigma_{cr} = \frac{\pi^2 E}{12(1-\nu^2)} \left(\frac{t}{b}\right)^2 k$ (3)

where $E = 28{,}300$ lb./in.$^2$

$\nu = 0.3$

$a = 13.313$ in.

$b = 56.25$ in.

$\alpha = \frac{a}{b} = 0.237$

$k = \left(\frac{\alpha}{n} + \frac{n}{\alpha}\right)^2$ for plates simply supported on all four edges

$n = 1$

$k = \left(\frac{0.237}{1} + \frac{1}{0.237}\right)^2 = 19.90$

$\sigma_{cr} = 161{,}000\ t^2$

| Plate No. | $\sigma_{cr}$ (psi) |
|---|---|
| 1 | 3790 |
| 2 | 3840 |
| 3 | 3840 |
| 4 | 3820 |

10. Modulus of Elasticity

For specimen number 1:

$\ell = 2.547$ in. Huggenberger G. F. (#1) = 1051

$w = 0.8435$ in. Huggenberger G. F. (#2) = 1040

$t = 0.1572$ in.

At P = 0: $R_1 = 1.55$

$R_2 = 1.51$

At P = 2160 lbs.: $R_1 = 1.09$

$R_2 = 0.86$

$$\sigma = \frac{P}{b't} = \frac{2.16}{(0.8435)(0.1572)} = 16.28 \text{ k.s.i.}$$

$$\varepsilon_1 = \frac{1.55 - 1.09}{1051} = 437.5 \text{ microinches/inch}$$

$$\varepsilon_2 = \frac{1.51 - 0.86}{1040} = 625 \text{ microinches/inch}$$

$$\varepsilon = \frac{\varepsilon_1 + \varepsilon_2}{2} = 531 \text{ microinches/inch}$$

From a composite plot of all three specimens

$$E = \frac{\Delta\sigma}{\Delta\varepsilon} = \frac{40.0}{1.415 \times 10^{-6}} = 28{,}300 \text{ k.s.i.}$$

## E. SUPPLEMENTARY DISCUSSION

### 1. Comparison of Methods for Determining $\sigma_{cr}$

The "top-of-the-knee" method gives values which are lower than the theoretical buckling stresses and are also the lowest given by any experimental analysis except for the strain-reversal method which was not usable in this case. This is in line with previous experience that this method gives low values whenever there is appreciable initial unfairness. To obtain better results it is necessary to apply the method to a series of plots for plates of the same size but having different initial deflections. If a line is then drawn through the tangent intersections and extrapolated to the $\sigma$-axis, the intercept represents the critical stress for a plate of zero initial deflection. This method was not usable for the series of plates tested in this work since there appeared to be no well-defined line through the points. A further difficulty in using the "top-of-the-knee" method is that a large number of points must be taken around the buckling point, and even then the upper tangent may be somewhat difficult to draw.

This same difficulty is inherent in Yoshiki's method, although the difficulty of drawing the tangent is reduced if a sufficient number of points are taken, and the knee appears sharper.

The Southwell method [48] and Donnell's variation [18] are based upon column theory rather than plate theory. However, these methods can be applied to some plate situations, especially when the aspect ratio is small and the $\frac{a}{t}$ ratio is large as is true for this case. For other plates these methods may be invalid, but the fact that the plots are straight lines for the present tests is strong evidence that the results are good.

In any event, either method may be helpful in that additional points can be taken from the straight line plot and used to more fully define the $\sigma$-d curve when the "top-of-the-knee" or Koshiki's method is used. Donnell's method seems somewhat preferable when it can be used since the plotted points are evenly spaced (for even increments of load) and since the critical load can be read directly as the intercept on the P-axis.

2. Deflection Measurements

During the tests numerous lateral deflection measurements were made along the plate, using the planed edge of the angle connecting the "a"-edge supports as the reference line. These proved to be practically useless, since the plate adjusted itself in the early stages of loading, and the deflections for the lower loads did not reflect bending in the plate. Attempts to use these values when making buckling analyses generally failed.

A far better measurement of the lateral deflections in the plate was the difference of the strains in opposite pairs of gages. These differences are directly proportional to the moment, and when the deformation of the plate is sinusoidal, they are proportional to the lateral deflection. These values are free of the effects of any lateral movement (without bending) which might occur as the plate adjusts itself to fit in the grooves in the loading bar. Furthermore, these readings do not reflect residual stresses which may be present in the plate.

Initial deflections were measured at various points on the four plates prior to placing them in the test apparatus. This was accomplished by laying a straight edge across the short dimension of the plate, and measuring the largest unfairness with a feeler gage. A plot

of the unfairness along the plate's horizontal centerline did not define any simple curve such as a sine curve. Thus it was impossible to consider these measurements as anything other than an indication of the approximate magnitude of equivalent unfairness. The extrapolated values of $d_o$ taken from the Donnell and Southwell plots compare fairly well with these measured values except for the case of Plate No. 1. (See Table IIIB). In the case of Plate No. 1, the measured values were especially dubious since it was necessary to block the plate into place prior to loading in order to make the long edges approximately straight. The extremely complex initial curvature affected not only the equivalent initial unfairness but apparently made the plate more resistant to buckling, probably since more energy was required to produce the final sinusoidal configuration.


3. Calibration of the Testing Machine

During most of the tests a 0-1000 lb. gage was connected to the upper manifold and the pressure recorded along with the other data. The gage was calibrated at several points and the results plotted. (See Fig. 35) To obtain an equivalent gage pressure as indicated by the testing machine gages, the total indicated load was divided by the total jack ram area of one set of jacks. As can be seen from Fig. 35 the difference at 20,000 lbs. indicated load on the testing machine, and integrated jack loading is about 615 lbs. Extrapolated to 30,000 lbs., the approximate range of ultimate plate loads, this difference becomes about 925 lbs.

If we analyse a free body diagram of a jack it is possible to draw some conclusions about this observed difference in readings.

FIG. 35

CALIBRATION OF TESTING MACHINE








FIG. 36




FREE BODY DIAGRAM
FORCES ON A HYDRAULIC
JACK

From Fig. 36 we can write the following equations:

$$P = P_i A_j - S + F \qquad (12)$$

$$P' = P_i A_j - S + F \qquad (13)$$

where

$P$ = total load on I-beam, (lbs.)

$P'$ = total load on edge of test plate, (lbs.)

$P_i$ = jack internal hydraulic pressure, (psi)

$A_j$ = total piston area of seven jacks, (sq. in.)

$S$ = total return spring force of seven jacks, (lbs.)

$F$ = total friction force between jack rams and jack cylinders (lbs.)

Under the conditions which prevailed when gage readings were taken the rams could move only inward since the hand pump was not in use. Hence, the direction of the friction force, $F$, is known.

From equations (12) and (13) we have:

$$P = P' \quad \text{and}$$

$$P - P_i A_j = F - S$$

Unfortunately the pressure gage attached to the jack manifold was not sensitive enough at or near zero readings to give a value for $S$ at different jack extensions.

The results indicate however that if the testing machine gage is a true measure of the load, $P$,

$$P > P_i A_j \qquad \text{or}$$

$$P - P_i A_j > 0 \qquad \text{hence}$$

$$F - S > 0 \qquad \text{or}$$

$$F > S$$

This result is absurd when $P_i \approx 0$ since the spring force does indeed overcome jack friction and return the rams to the initial position.

$$P = P_0 \qquad \text{and}$$

$$S - T_1 V_1^2 = S - S$$

Furthermore the pressure plate attached to the jack ensured the

at different jack extensions.

The results indicate however that if this testing machine plate is

a true measure of the load, $P$,

$$P > P_1 V_1^2 \qquad \text{or}$$

$$P - P_1 V_1^2 > 0 \qquad \text{hence}$$

$$S - S > 0 \qquad \text{or}$$

$$S > T$$

This result is almost when $V_1^2 = 0$ since the applied force does indeed

overcome jack friction and reduce the rate to the initial position.

Where $P_0$. If we now write the following equations:

$$P = P_1 V_1^2 - S + P \tag{12}$$

$$P_0 = P_1 V_1^2 - S + P \tag{13}$$

where

$P$ = *total load on I-beam* (lbs.)

$P_0$ = *total load on edge of test plate*. (lbs.)

$V_1^2$ = *jack fractional deformation pressure*. (in.)

$V_1^1$ = *total platen area of screw jacks*. (sq. in.)

$S$ = *total reduce spring force of screw jacks*. (lbs.)

$T$ = *total friction force between jack ram and jack cylinders* (lbs.)

Under the conditions which previously when jack readings were taken the

ram would move only fractional where the load cell was not in use. Since

the direction of the friction force, $T$ is known.

From equations (12) and (13) we have:

The validity of this inequality when $P_j$ is large, cannot be judged accurately from the known data. However, the analysis shows that the observations of Fig. 35 are possible, i.e., that the testing machine gage readings may be correct, but the results also cast reasonable doubt on this assumption. On this basis the authors requested that the gages of machine No. 105 be calibrated at least at one load, 20,000 lbs. It was found that the last calibration test was performed in April, 1950. Unfortunately the calibration was not completed in time for inclusion in this thesis but such a confirmation should be made prior to future buckling tests.


## F. DETERMINATION OF YOUNG'S MODULUS

To determine the modulus of elasticity of the test specimens in compression, a compression jig using the single plate method described and built by Polychrome [40] was used.

Briefly the jig consists of a frame which holds the guide plates and specimen in place and contains a subpress in the form of a plunger which bears on the specimen. The steel guide plates are milled with triangular grooves which run the length of the specimen. The grooves opposite each other in the guide plates are staggered so that lateral extension of the specimen is permitted when a load is applied. Two Huggenberger strain gages of one inch base length are attached to opposite edges of the specimen through apertures in the frame. Guide plate pressure and centering is accomplished by adjusting two 3/8" knurled screws until they are just hand tight.

The specimens were rough cut from the same plate and in the same direction as were the test plates. Test plates and compression specimens received the same surface preparation such as sand- or shot-blasting or pickling.

Three specimens were prepared and milled to the final dimensions. The thickness was determined in the same manner as that described for the test plates. All specimens were of the same length and width, 0.8435" x 2.547" which conform to the ASTM standards of a 1 to 3 proportion. (Designation E9-33T) The results of the three tests are given in Fig. 37. There are several possible sources of error in this procedure. The grooved guide plates do not permit complete freedom of lateral extension. This has effect primarily on the determination of the


50
45
40
35
30
25
20
15
10
5
0
σ (KIPS/SQUARE INCH)
0
500
1000
1500
2000
2500
3000
3500
ε (MICROINCHES/INCH)
E = 28,300 KIPS/IN²
COMPRESSION STRESS-STRAIN PLOT
FOR 1020 STEEL (SHIP PLATE)
(SPECIMENS CUT FROM SAME PLATE AS TEST PLATES NOS. 1-4)
SPECIMEN NO. 1
SPECIMEN NO. 2
SPECIMEN NO. 3
5/10/54 MP

yield point. There is a friction force developed between the specimen and its guide plates and also between the plunger and its guides, particularly if the loading should be uneven. Since the surface of these specimens was quite rough, care was taken not to tighten the knurled screws excessively especially since the prime result expected was the modulus rather than an accurate yield point. It should be noted however that such a friction force would tend to raise the value of E. Since the value of E found was slightly below that which one would normally expect for the type of steel tested, it is probable that the effect of such friction was not large and was reasonably constant for all tests.

The variations occuring in the stress-strain curve above the proportional limit are probably caused by unevenness in the load distribution across the loaded edge of the specimen. If one side was loaded more heavily than the other, the strain on that side would reach the proportioned limit before the other side and cause the curve to become more linear at various loads depending on the degree of unevenness. The points recorded above its proportioned limit were recorded after reasonable yielding had taken place but no attempt was made to wait until final values of the load and its strain were recorded. For this particular study an accurate value of the yield point is not necessary. It was felt that there was no need to pursue this phenomenon further. It is believed, however, in the future development of this test program, an accurate value of the yield stress will become important to the analysis of the data. Hence, the reasons for these variations should be pursued.

Specifications of Compression Test Procedure

Test Specimens: Cut from same plate at best plates and in the same direction. Milled to 2.547 x 0.505 inches. Three specimens tested.

Strain Gages: Two Type A Huggenberger - 1 inch gage length
No. 2195 Gage Factor 1051
No. 2201 Gage Factor 1041

Testing Machine: Testing Materials Lab. #203
Manufacturer - Riehle' Bros.
Capacity - 20,000 pounds
Specimens held in compression jig.
Spherical head used.

Test Procedure: Knurled bolts holding guide plates were tightened barely hand tight. Load of about 200 pounds applied and released several times to check zero readings on Huggenberger gages. Load applied in increments of approximately 500 pounds. Gages read at each step. Modulus of elasticity found by plotting stress vs. strain.

# APPENDIX G

## ORIGINAL DATA

## TABLE IV

### Data Sheet

Date: 29 March 1954
Test No: 2
Plate No.: 1
Strain Indicator
Serial No. D58130
Type K
G.F. Setting 2.01

B-Edge Conditions

Load Application - Machine
Jacks
Bar - 3/4" (Grooved)
Gasket - Neoprene

No Segments
No Shims

| Load (Kips) | Zero | 2 | 4 | 6 | 8 | 10 | 12 | 14 | Final Zero |
|---|---|---|---|---|---|---|---|---|---|
| Gage | | | | Strain Indicator Readings (microinches/inch) | | | | | |
| 1 | 8-608 | 592 | 589 | 589 | 582 | 574 | 568 | 564 | 604 |
| 2 | 7-177 | 155 | 158 | 152 | 150 | 145 | 141 | 136 | 177 |
| 3 | 9-249 | 210 | 205 | 200 | 197 | 190 | 187 | 180 | 252 |
| 4 | 4-407 | 401 | 395 | 385 | 376 | 363 | 357 | 343 | 400 |
| 5 | 8-752 | 736 | 736 | 725 | 721 | 711 | 708 | 707 | 754 |
| 6 | 7-737 | 730 | 728 | 720 | 718 | 710 | 706 | 691 | 741 |
| 7 | 6-782 | 788 | 792 | 783 | 770 | 749 | 721 | 691 | 783 |
| 8 | 5-557 | 535 | 531 | 538 | 542 | 552 | 570 | 582 | 562 |
| 9 | 7-179 | 191 | 184 | 171 | 152 | 141 | 128 | 107 | 188 |
| 10 | 8-866 | 821 | 810 | 800 | 795 | 790 | 791 | 792 | 870 |
| 11 | 6-651 | 666 | 664 | 662 | 662 | 659 | 660 | 657 | 657 |
| 12 | 6-1017 | 972 | 966 | 960 | 952 | 944 | 940 | 930 | 1020 |
| 13 | 8-873 | 850 | 847 | 841 | 840 | 836 | 836 | 833 | 880 |
| 14 | 9-267 | 261 | 250 | 240 | 230 | 220 | 208 | 193 | 270 |
| 15 | 7-423 | 380 | 380 | 376 | 372 | 367 | 365 | 361 | 426 |
| 16 | 7-907 | 1067 | 1077 | 1071 | 1069 | 1061 | 1058 | 1050 | 1050* |
| 17 | 8-830 | 797 | 796 | 791 | 790 | 787 | 787 | 783 | 837 |
| 18 | 9-242 | 272 | 269 | 264 | 260 | 250 | 241 | 230 | 246 |
| 19 | 6-1000 | 970 | 962 | 957 | 953 | 948 | 950 | 947 | 1009 |
| 20 | 7-714 | 740 | 732 | 720 | 710 | 694 | 682 | 668 | 718 |
| 21 | 9-121 | 090 | 079 | 071 | 067 | 059 | 054 | 053 | 128 |
| 22 | 8-200 | 220 | 210 | 201 | 190 | 178 | 168 | 148 | 201 |
| 23 | 7-1060 | 1022 | 1013 | 1008 | 1002 | 996 | 992 | 992 | 1066 |
| 24 | 8-411 | 426 | 418 | 408 | 400 | 390 | 382 | 367 | 412 |
| 25 | 8-936 | 891 | 887 | 880 | 875 | 868 | 863 | 856 | 911 |
| 26 | 8-341 | 347 | 332 | 320 | 310 | 297 | 287 | 273 | 342 |
| 27 | 6-850 | 790 | 780 | 768 | 760 | 751 | 749 | 745 | 856 |
| 28 | 7-911 | 920 | 913 | 902 | 894 | 882 | 870 | 857 | 911 |
| 29 | 7-198 | 161 | 157 | 148 | 141 | 134 | 128 | 121 | 202 |
| 30 | 7-762 | 766 | 762 | 758 | 755 | 750 | 747 | 738 | 762 |
| 31 | 7-460 | 454 | 450 | 447 | 441 | 435 | 430 | 420 | 462 |
| 32 | 8-117 | 095 | 091 | 088 | 087 | 082 | 082 | 080 | 118 |
| 33 | 8-651 | 655 | 641 | 629 | 617 | 600 | 580 | 557 | 653 |
| 34 | 5-985 | 952 | 952 | 947 | 945 | 944 | 949 | 953 | 987 |
| 35 | 4-750 | 758 | 738 | 722 | 705 | 679 | 644 | 595 | 750 |
| 36 | 6-1030 | 1010 | 1034 | 1034 | 1047 | 1061 | 1090 | 1130 | 1040 |

TABLE IV

Data Sheet

Date: 29 March 1954
Test No.: 7 (contd.)
Plate No.: 1
Strain Indicator
Serial No. D58130
Type K
C.F. Setting 2.01

B-Edge Conditions

Load Application - Machine
Jacks
Bar - 3/4" (Grooved)
Gasket - Neoprene

No Segments
No Shims

| Load (kips) | Zero | 2 | 4 | 6 | 8 | 10 | 12 | 14 | Final Zero |
|---|---|---|---|---|---|---|---|---|---|
| | | | | Strain Indicator Readings (microinches/inch) | | | | | |
| Gage | | | | | | | | | |
| 37 | 6-521 | 510 | 524 | 534 | 548 | 557 | 573 | 570 | 525 |
| 38 | 7-479 | 461 | 448 | 428 | 407 | 380 | 348 | 336 | 480 |
| 39 | 8-443 | 457 | 458 | 460 | 466 | 470 | 472 | 475 | 446 |
| 40 | 8-457 | 439 | 429 | 413 | 400 | 383 | 365 | 351 | 459 |
| 41 | 8-1000 | 988 | 980 | 970 | 968 | 964 | 960 | 952 | 1007 |
| 42 | 8-952 | 937 | 923 | 910 | 900 | 891 | 882 | 880 | 958 |
| 43 | 8-258 | 243 | 232 | 218 | 202 | 182 | 162 | 143 | 263 |
| 44 | 7-557 | 563 | 561 | 564 | 571 | 578 | 587 | 591 | 560 |
| 45 | 8-173 | 151 | 142 | 130 | 119 | 103 | 090 | 071 | 180 |
| 46 | 7-719 | 740 | 747 | 747 | 750 | 751 | 758 | 760 | 725 |
| 47 | 8-718 | 726 | 711 | 698 | 683 | 667 | 649 | 630 | 755 |
| 48 | 7-086 | 078 | 083 | 088 | 092 | 096 | 100 | 105 | 083 |
| 49 | 7-410 | 380 | 367 | 349 | 330 | 310 | 290 | 269 | 416 |
| 50 | 7-284 | 272 | 276 | 280 | 288 | 296 | 308 | 316 | 252 |
| 51 | 7-540 | 521 | 513 | 504 | 498 | 487 | 475 | 462 | 548 |
| 52 | 4-820 | 836 | 841 | 842 | 843 | 842 | 824 | 818 | 828 |
| 53 | 6-390 | 367 | 358 | 329 | 312 | 295 | 278 | 255 | 396 |
| 54 | 7-377 | 376 | 460 | 438 | 370 | - | 336 | 335 | 352 |
| 55 | 7-800 | 794 | 770 | 740 | 710 | 674 | 639 | 604 | 838 |
| 56 | 6-223 | 213 | 252 | 259 | 271 | 286 | 302 | 318 | 226 |
| 57 | 8-976 | 970 | 906 | 890 | 876 | 858 | 840 | 820 | 983 |
| 58 | 6-410 | 430 | 436 | 438 | 444 | 450 | 459 | 465 | 411 |
| 59 | 7-1020 | 962 | 940 | 935 | 920 | 900 | 880 | 866 | 1020 |
| 60 | 8-477 | 507 | 511 | 517 | 521 | 524 | 528 | 530 | 480 |
| 61 | 7-954 | 514 | 503 | 488 | 470 | 453 | 438 | 419 | 961 |
| 62 | 5-670 | 686 | 682 | 680 | 682 | 682 | 684 | 688 | 675 |
| 63 | 8-641 | 637 | 638 | 630 | 625 | 621 | 623 | 620 | 647 |
| 64 | 8-333 | 341 | 330 | 323 | 317 | 305 | 289 | 282 | 339 |

Deflection Readings at 14 kips Load
(from a reference line)

| Gage Position | Reading |
|---|---|
| 1 | 0.3632-.0020 |
| 3 | 0.3915-.0015 |
| 5 | 0.2980-.0060 |

TABLE V

Data Sheet

Date: 31 March 1954
Test No.: 5
Plate No.: 1
Strain Indicator
Serial No. D58130
Type K
S.F. Setting 2.01

B-Edge Conditions

Load Application - Machine No Segments
Jacks No Shims
Bar - 3/4" (Flat)
Gasket - Single Solder 3/32" diam. (new)

| Load (kips) | 2 | 20 | Zero | 10 | 20 | Gage | Zero | 10 | 20 |
|---|---|---|---|---|---|---|---|---|---|
| PI | 60 | 520 | 0 | 250 | 520 | | 0 | 250 | 520 |
| Gage | d (inches) | | Strain Indicator Reading | | | | (microinches/inch) | | |
| 7 | .315* | .325* | 6-803 | 660 | 521 | 37 | 6-520 | 674 | 705 |
| 8 | | | 5-536 | 561 | 620 | 38 | 7-467 | 240 | 150 |
| 9 | .318 | .335 | 7-200 | 224 | 105 | 39 | 8-460 | 447 | 429 |
| 10 | | | 8-861 | 870 | 818 | 40 | 8-454 | 392 | 323 |
| 11 | .322 | .356 | 6-646 | 610 | 484 | 41 | 8-1002 | 977 | 979 |
| 12 | | | 6-1020 | 977 | 878 | 42 | 8-957 | 912 | 867 |
| 13 | .341 | .400 | 8-872 | 846 | 851 | 43 | 7-1262 | 1206 | 1207 |
| 14 | | | 9-269 | 249 | 187 | 44 | 7-560 | 559 | 508 |
| 15 | .362 | .435 | - | - | - | 45 | 7-1180 | 1139 | 1120 |
| 16 | | | - | - | - | 46 | 7-720 | 720 | 663 |
| 17 | .360 | .434 | 8-832 | 881 | 932 | 47 | 8-748 | 715 | 666 |
| 18 | | | 8-1240 | 1184 | 1016 | 48 | 6-1051 | 1014 | 980 |
| 19 | .350 | .420 | 6-1000 | 1051 | 1092 | 49 | 7-414 | 420 | 430 |
| 20 | | | 7-710 | 562 | 429 | 50 | 6-1249 | 1186 | 1142 |
| 21 | .319 | .375 | - | - | - | 51 | 7-504 | 496 | 490 |
| 22 | | | - | - | - | 52 | 4-815 | 791 | 749 |
| 23 | .307 | .318 | 7-1060 | 975 | 994 | 53 | 6-397 | 321 | 267 |
| 24 | | | 8-402 | 418 | 336 | 54 | 7-343 | 340 | 302 |
| 25 | .292 | .257 | 8-930 | 869 | 834 | 55 | 7-837 | 753 | 711 |
| 26 | | | 8-333 | 341 | 278 | 56 | 8-212 | 218 | 196 |
| 27 | .267 | .206 | 6-818 | 774 | 718 | 57 | 8-987 | 908 | 830 |
| 28 | | | 7-903 | 890 | 850 | 58 | 6-384 | 398 | 411 |
| 29 | .237 | .223 | 6-1198 | 1140 | 1110 | 59 | 7-1021 | 827 | 681 |
| 30 | | | 7-753 | 733 | 673 | 60 | 8-473 | 509 | 609 |
| 31 | .211 | .194 | 7-487 | 370 | 309 | 61 | 7-558 | 426 | 313 |
| 32 | | | 7-1112 | 1107 | 1009 | 62 | 5-666 | 733 | 776 |
| 33 | .219 | .190 | 8-650 | 586 | 504 | | | | |
| 34 | | | 5-971 | 977 | 997 | | | | |
| 35 | .231* | .225* | 4-773 | 495 | 152 | | | | |
| 36 | | | 6-990 | 1180 | 1140 | | | | |

* Readings taken between gage positions 7 & 9 or 33 & 35

Gage pairs 15, 16; 21,22; 63, 64; 65, 66 - no readings

| | | |

TABLE VI

Data Sheet

Date: 11 April 1954 B-Edge Condition
Test No.: 12
Plate No.: 1 Load Application - Pump Segments
Strain Indicator Jacks Shims
Serial No. D58130 Bar - 1/8"
Type K Gasket: Double Solder 1/16" diam. ( )
G.F. Setting 2.01 Remarks: Plate reversed on a diagonal

| Load (kips) | 20 | Zero | 2 | 10 | 20 | Gage | Zero | 2 | 10 | 20 |
|---|---|---|---|---|---|---|---|---|---|---|
| Gage | d (in.) | | Strain Indicator Reading (microinches/inch) | | | | | | | |
| 7 | .196* | 6-793 | 767 | 769 | 774 | 37 | 6-502 | 504 | 540 | 597 |
| 8 | | 5-540 | 553 | 533 | 534 | 38 | 7-464 | 452 | 399 | 334 |
| 9 | .145 | 7-302 | 276 | 264 | 247 | 39 | 8-447 | 450 | 463 | 481 |
| 10 | | 8-827 | 821 | 773 | 729 | 40 | 8-435 | 402 | 341 | 260 |
| 11 | .096 | 6-641 | 636 | 648 | 670 | 41 | 8-990 | 991 | 997 | 1011 |
| 12 | | 6-1022 | 1007 | 983 | 948 | 42 | 8-945 | 937 | 912 | 869 |
| 13 | .089 | 8-861 | 848 | 851 | 872 | 43 | 8-242 | 230 | 230 | 238 |
| 14 | | 9-264 | 245 | 190 | 114 | 44 | 7-561 | 549 | 497 | 440 |
| 15 | .102 | 7-411 | 403 | 420 | 457 | 45 | 7-1163 | 1159 | 1160 | 1161 |
| 16 | | 7-900 | 907 | 876 | 841 | 46 | 7-726 | 724 | 710 | 685 |
| 17 | .137 | 8-815 | 795 | 797 | 819 | 47 | 8-730 | 719 | 699 | 696 |
| 18 | | 8-1251 | 1238 | 1190 | 1119 | 48 | 6-1061 | 1046 | 1003 | 958 |
| 19 | .172 | 6-990 | 978 | 990 | 1025 | 49 | 7-390 | 382 | 373 | 379 |
| 20 | | 7-723 | 720 | 704 | 674 | 50 | 7-254 | 254 | 246 | 234 |
| 21 | .210 | 8-1103 | 1088 | 1085 | 1098 | 51 | 7-520 | 490 | 455 | 430 |
| 22 | | 7-582 | 578 | 531 | 465 | 52 | 4-816 | 820 | 793 | 754 |
| 23 | .276 | 7-1041 | 1034 | 1040 | 1059 | 53 | 6-375 | 367 | 352 | 349 |
| 24 | | 8-402 | 403 | 389 | 361 | 54 | 7-340 | 344 | 337 | 330 |
| 25 | .298 | 8-916 | 898 | 887 | 879 | 55 | 7-809 | 796 | 757 | 718 |
| 26 | | 8-336 | 325 | 209 | 236 | 56 | 7-1204 | 1191 | 1166 | 1141 |
| 27 | .302 | 6-831 | 835 | 832 | 839 | 57 | 8-960 | 960 | 944 | 930 |
| 28 | | 7-895 | 881 | 872 | 858 | 58 | 6-367 | 340 | 352 | 351 |
| 29 | .266 | 6-1184 | 1185 | 1159 | 1135 | 59 | 7-994 | 988 | 968 | 902 |
| 30 | | 7-744 | 720 | 700 | 670 | 60 | 8-453 | 439 | 418 | 395 |
| 31 | .226 | 7-447 | 445 | 451 | 454 | 61 | 7-525 | 521 | 509 | 492 |
| 32 | | 7-1099 | 1095 | 1080 | 1070 | 62 | 5-646 | 647 | 647 | 652 |
| 33 | .212 | 8-630 | 621 | 645 | 644 | 63 | 8-643 | 620 | 583 | 530 |
| 34 | | 5-903 | 959 | 875 | 815 | 64 | 8-309 | 305 | 286 | 277 |
| 35 | .207* | 4-683 | 669 | 716 | 740 | 65 | 7-705 | 711 | 699 | 662 |
| 36 | | 6-1043 | 1054 | 1000 | 974 | 66 | 7-703 | 694 | 695 | 707 |

* Readings taken between gages 7 & 9 or 33 & 35

[illegible]

[illegible]

[illegible]

TABLE VII

Data Sheet

Date: 12 April 1954 B-Edge Condition
Test No.: 14
Plate No.: 1 Lead Application - Pump Segments
Strain Indicator Jacks Shims
Serial No. D58130 Bar - 3/4" (Flat)
Type K Gasket - Double Solder 1/16" diam. (new)
G.F. Setting 2.01 Remark: Repeatability Run

| Load (kips) | Zero | 2 | 10 | 20 | Gage | Zero | 2 | 10 | 20 | 20 |
|---|---|---|---|---|---|---|---|---|---|---|
| Gage | Strain Indicator Reading (microinches/inch) | | | | | | | | | d (inches) |
| 7 | 6-814 | 783 | 765 | 670 | 37 | 6-520 | 528 | 588 | 618 | .193* |
| 8 | 5-553 | 541 | 524 | 570 | 38 | 7-477 | 464 | 376 | 278 | |
| 9 | 7-315 | 303 | 263 | 240 | 39 | 8-462 | 470 | 467 | 469 | .199 |
| 10 | 8-843 | 837 | 814 | 727 | 40 | 8-457 | 450 | 396 | 322 | |
| 11 | 6-650 | 649 | 648 | 639 | 41 | 8-1005 | 1012 | 986 | 972 | .213 |
| 12 | 6-1024 | 1019 | 971 | 907 | 42 | 8-963 | 940 | 890 | 813 | |
| 13 | 8-871 | 873 | 862 | 877 | 43 | 8-1263 | 260 | 242 | 232 | .257 |
| 14 | 9-278 | 260 | 186 | 090 | 44 | 7-578 | 557 | 520 | 455 | |
| 15 | 7-424 | 419 | 427 | 468 | 45 | 7-1179 | 1172 | 1160 | 1167 | .286 |
| 16 | 7-908 | 891 | 844 | 760 | 46 | 7-743 | 719 | 681 | 626 | |
| 17 | 8-829 | 828 | 816 | 823 | 47 | 8-747 | 747 | 728 | 718 | .283 |
| 18 | 8-1262 | 1260 | 1207 | 1110 | 48 | 6-1078 | 1071 | 1040 | 997 | |
| 19 | 6-1003 | 997 | 990 | 1019 | 49 | 7-409 | 396 | 362 | 340 | .262 |
| 20 | 7-732 | 727 | 667 | 582 | 50 | 7-268 | 260 | 221 | 158 | |
| 21 | 8-1120 | 1110 | 1102 | 1118 | 51 | 7-539 | 531 | 491 | 459 | .208 |
| 22 | 7-594 | 583 | 532 | 450 | 52 | 4-840 | 837 | 814 | 774 | |
| 23 | 7-1050 | 1050 | 1047 | 1044 | 53 | 6-390 | 368 | 312 | 249 | .164 |
| 24 | 8-424 | 400 | 372 | 299 | 54 | 7-358 | 346 | 327 | 293 | |
| 25 | 8-928 | 923 | 883 | 868 | 55 | 7-826 | 791 | 720 | 637 | .123 |
| 26 | 8-353 | 343 | 296 | 220 | 56 | 7-1224 | 1209 | 1178 | 1136 | |
| 27 | 6-862 | 857 | 810 | 777 | 57 | 8-975 | 967 | 919 | 862 | .102 |
| 28 | 7-911 | 896 | 842 | 791 | 58 | 6-390 | 390 | 370 | 350 | |
| 29 | 6-1202 | 1205 | 1180 | 1150 | 59 | 7-1012 | 1010 | 968 | 922 | .079 |
| 30 | 7-759 | 755 | 730 | 679 | 60 | 8-471 | 469 | 460 | 443 | |
| 31 | 7-468 | 470 | 440 | 417 | 61 | 7-544 | 540 | 508 | 469 | .082 |
| 32 | 7-1110 | 1108 | 1076 | 1044 | 62 | 5-660 | 661 | 653 | 641 | |
| 33 | 8-698 | 698 | 661 | 640 | 63 | 8-663 | 660 | 609 | 492 | .141 |
| 34 | 5-967 | 963 | 900 | 841 | 64 | 8-385 | 317 | 290 | 269 | |
| 35 | 4-701 | 702 | 822 | 804 | 65 | 7-732 | 698 | 692 | 682 | .173* |
| 36 | 6-1072 | 1022 | 969 | 830 | 66 | 7-715 | 719 | 682 | 632 | |

* Readings taken between gages 37 & 39 or 63 & 65

## TABLE VIII

### Data Sheet

Date: 14 April 1954
Test No.: 16
Plate No.: 1
Strain Indicator
Serial No. D58130
Type K
G.F. Setting 2.04

B-Edge Conditions

Load Application - Pump
No Jacks
Bar - 3/4" (flat)
Gasket - Double Solder
1/16" diam. (new)

Segments
Shims

| Load (kips) | Zero | 2 | 10 | 20 | Gage | Zero | 2 | 10 | 20 |
|---|---|---|---|---|---|---|---|---|---|
| Gage | | | | | | | | | |
| 7 | 6-827 | 820 | 835 | 814 | 37 | 6-582 | 616 | 664 | 672 |
| 8 | 5-520 | 515 | 418 | 362 | 38 | 7-371 | 325 | 231 | 145 |
| 9 | 7-294 | 280 | 277 | 248 | 39 | 8-433 | 441 | 442 | 438 |
| 10 | 8-757 | 750 | 726 | 657 | 40 | 8-398 | 373 | 332 | 285 |
| 11 | 6-646 | 637 | 625 | 620 | 41 | 8-958 | 947 | 920 | 906 |
| 12 | 6-1002 | 991 | 952 | 892 | 42 | 8-905 | 884 | 826 | 747 |
| 13 | 8-833 | 832 | 825 | 830 | 43 | 7-1230 | 1223 | 1205 | 1198 |
| 14 | 8-1224 | 1217 | 1174 | 1119 | 44 | 7-538 | 521 | 477 | 413 |
| 15 | 7-4[illegible] | 409 | 396 | 408 | 45 | 7-1143 | 1141 | 1120 | 1121 |
| 16 | 7-[illegible]70 | 861 | 798 | 725 | 46 | 7-700 | 680 | 641 | 597 |
| 17 | 8-788 | 791 | 800 | 812 | 47 | 8-701 | 690 | 670 | 660 |
| 18 | 8-1202 | 1187 | 1148 | 1080 | 48 | 6-1046 | 1033 | 998 | 948 |
| 19 | 6-988 | 981 | 970 | 971 | 49 | 7-381 | 372 | 347 | 338 |
| 20 | 7-697 | 691 | 619 | 533 | 50 | 7-234 | 230 | 203 | 171 |
| 21 | 8-1067 | 1064 | 1062 | 1071 | 51 | 7-507 | 496 | 451 | 406 |
| 22 | 7-559 | 567 | 527 | 461 | 52 | 4-842 | 835 | 811 | 767 |
| 23 | 7-1015 | 1015 | 1009 | 1007 | 53 | 6-370 | 352 | 308 | 248 |
| 24 | 8-383 | 391 | 360 | 301 | 54 | 7-333 | 331 | 310 | 278 |
| 25 | 8-867 | 864 | 838 | 792 | 55 | 7-777 | 761 | 708 | 625 |
| 26 | 8-320 | 311 | 265 | 170 | 56 | 7-1194 | 1190 | 1162 | 1134 |
| 27 | 6-813 | 807 | 770 | 745 | 57 | 8-910 | 899 | 852 | 807 |
| 28 | 7-[illegible]88 | 890 | 852 | 804 | 58 | 6-384 | 377 | 366 | 360 |
| 29 | 6-1165 | 1163 | 1155 | 1144 | 59 | 7-964 | 955 | 910 | 858 |
| 30 | 7-734 | 738 | 720 | 703 | 60 | 8-436 | 433 | 422 | 419 |
| 31 | 7-430 | 424 | 392 | 361 | 61 | 7-504 | 486 | 430 | 370 |
| 32 | 7-1080 | 1079 | 1048 | 1010 | 62 | 5-662 | 670 | 665 | 675 |
| 33 | 8-[illegible]01 | 817 | 586 | 562 | 63 | 8-610 | 542 | 467 | 350 |
| 34 | 5-948 | 945 | 872 | 812 | 64 | 7-1291 | 1281 | 1261 | 1260 |
| 35 | 1-711 | 800 | 842 | 807 | 65 | 7-678 | 550 | 486 | 326 |
| 36 | 6-1043 | 847 | 727 | 647 | 66 | 7-702 | 722 | 702 | 751 |

Page Three

| | | |

TABLE IX

Data Sheet

Date: 14 April 1954
Test No.: 16 (continued)
Plate No.: 1
Strain Indicator
Serial No. D58130
Type K
G.F. Setting 2.04

B-Edge Conditions

Load Application - Pump
No Jacks
Bar - 3/4" (flat)
Gasket - Double Solder
1/16" diam. (new)

Segments
Shims

| Load Kips Gage | Zero | 2 | 20 |
|---|---|---|---|
| | Deflection - d(inches) | | |
| 37 | .185* | .190* | .184* |
| 39 | .186 | .193 | .179 |
| 41 | .189 | .207 | .181 |
| 43 | .218 | .246 | .206 |
| 45 | .247 | .284 | .235 |
| 47 | .253 | .291 | .242 |
| 49 | .252 | .280 | .235 |
| 51 | .226 | .239 | .205 |
| 53 | .219 | .226 | .195 |
| 55 | .209 | .188 | .176 |
| 57 | .190 | .157 | .160 |
| 59 | .155 | .133 | .138 |
| 61 | .136 | .121 | .125 |
| 63 | .172 | .150 | .154 |

* Readings taken between gage positions 37 and 39.

TABLE X

Data Sheet

Date: 19 April 1954
Test No.: 19 (continued)
Plate No.: 1
Strain Indicator
Serial No. D58130
Type K
S.F. Setting 2.01

B-Edge Conditions

Load Application - Pump Jacks
Bar - 3/4" (flat)(1)
Gasket - Double Solder 1/16" diam.

Segments Shims

| Load Kips | Zero | 20 | | Zero | 20 |
|---|---|---|---|---|---|
| Gage | Strain | | Gage | Strain | |
| 7 | 6-651 | 1057 | 37 | 6-576 | 550 |
| 8 | 5-659 | 235 | 38 | 7-461 | 417 |
| 9 | 7-339 | 367 | 39 | 8-490 | 400 |
| 10 | 8-857 | 642 | 40 | 8-470 | 370 |
| 11 | 6-676 | 695 | 41 | 8-1028 | 961 |
| 12 | 6-1041 | 890 | 42 | 8-979 | 893 |
| 13 | 8-899 | 942 | 43 | 7-1288 | 1245 |
| 14 | 8-1793 | 1155 | 44 | 7-592 | 530 |
| 15 | 7-450 | 500 | 45 | 7-1204 | 1161 |
| 16 | 7-720 | 765 | 46 | 7-761 | 690 |
| 17 | 8-857 | 909 | 47 | 8-770 | 668 |
| 18 | 8-1269 | 1111 | 48 | 6-1089 | 990 |
| 19 | 6-1037 | 1030 | 49 | 7-433 | 305 |
| 20 | 7-733 | 563 | 50 | 6-1284 | 1200 |
| 21 | 8-1161 | 1130 | 51 | 7-558 | 475 |
| 22 | 7-582 | 466 | 52 | 4-860 | 802 |
| 23 | 7-1077 | 1024 | 53 | 6-404 | 341 |
| 24 | 8-450 | 371 | 54 | 7-388 | 350 |
| 25 | 8-943 | 833 | 55 | 7-836 | 712 |
| 26 | 8-381 | 301 | 56 | 7-1260 | 1209 |
| 27 | 6-802* | 760 | 57 | 8-986 | 820 |
| 28 | 7-943 | 892 | 58 | 6-428 | 396 |
| 29 | 6-1217 | 1097 | 59 | 7-1027 | 900 |
| 30 | 7-790 | 750 | 60 | 8-500 | 500 |
| 31 | 7-484 | 387 | 61 | — | — |
| 32 | 7-1140 | 1118 | 62 | — | — |
| 33 | 8-672 | 647 | 63 | — | — |
| 34 | 5-1002 | 859 | 64 | — | — |
| 35 | — | — | 65 | — | — |
| 36 | — | — | 66 | — | — |

* Doubtful reading.

(1) Pump in lower bar over bottom jack and under gages 17 and 18.

(1) Temp 25 Lower Dec even Eighteen Digit and number Digits 12 and 32.

TABLE XI

Data Sheet

Date: 19 April 1954
Test No.: 19
Plate No.: 1
Strain Indicator
Serial No. D581130
Type K
G.F. Setting 2.01

B-Edge Conditions

Load Application - Pump Jacks
Bar - 3/4" (flat)(1)
Gasket - Double Solder 1/16" diam.

Segments
Shims

| Gage | 3 | 4 | 67 | 68 |
|---|---|---|---|---|
| Load (kips) | Strain Indicator Reading (microinches/inch) | | | |
| Zero | 8-1384 | 4-500 | 7-1326 | 7-635 |
| 2 | 1360 | 505 | 1331 | 602 |
| 4 | 1364 | 484 | 1350 | 566 |
| 6 | 1368 | 463 | 1364 | 535 |
| 8 | 1370 | 443 | 1380 | 503 |
| 10 | 1373 | 421 | 1394 | 470 |
| 12 | 1378 | 398 | 1412 | 439 |
| 14 | 1382 | 374 | 1431 | 403 |
| 16 | 1390 | 346 | 1452 | 363 |
| 18 | 1401 | 317 | 1478 | 323 |
| 20 | 1417 | 280 | 1509 | 276 |
| 22 | 1438 | 239 | 1541 | 227 |
| 24 | 1468 | 182 | 1581 | 166 |
| 26 | 1510 | ( 120)<br>(3-1120) | 1641 | ( 91)<br>(6-1091) |
| 28 | 1580 | 1032 | 1706 | 1005 |
| 30 | 1678 | 910 | 1810 | 883 |
| 32 | ( 1813)<br>(9-930) | 617 | ( 1940)<br>(8-980) | 670 |
| 34 | 1220 | 318 | 1269 | 348 |
| 36 | 1995 | 2-320 | 1750 | 5-720 |

Maximum Load - 36.2 kips

(1) Gap in lower bar over bottom jack and under gages 17 and 18.

TABLE XII

Data Sheet

Date: 19 April 1954
Test No.: 20
Plate No.: 2
Strain Indicator
Serial No. D58130
Type K
G. F. Setting 2.01

B-Edge Conditions

Load Application - Pump Jacks
Bar - 3/4" (Flat)
Gasket - Double Solder 1/16" diam.
Segments Shims

| Gage Load | 11 | 22 | 3 | 4* | 5 | 6 | 7 | 8 | 9 | 10 |
|---|---|---|---|---|---|---|---|---|---|---|
| | Strain Indicator Reading (microinches/inch) | | | | | | | | | |
| Kips | 5- | 7- | 5- | 44- | 8- | 5- | 7- | 7- | 5- | 5- |
| Zero | 1202 | 818 | 1261 | 935 | 430 | 994 | 1017 | 564 | 911 | 1495 |
| 2 | 1182 | 841 | 1210 | 930 | 399 | 1010 | 988 | 574 | 882 | 1506 |
| 4 | 1165 | 845 | 1182 | 940 | 373 | 1024 | 955 | 586 | 844 | 1518 |
| 6 | 1143 | 847 | 1149 | 952 | 342 | 1044 | 920 | 602 | 828 | 1530 |
| 8 | 1122 | 850 | 1117 | 962 | 303 | 1064 | 880 | 622 | 801 | 1546 |
| 10 | 1093 | 854 | 1079 | 982 | 262 | 1097 | 830 | 648 | 767 | 1563 |
| 12 | 1067 | 867 | 1032 | 1011 | 211 | 1133 | 770 | 681 | 730 | 1588 |
| 14 | 1031 | 880 | 982 | 1057 | 152 | 1180 | 702 | 724 | 682 | 1619 |
| 16 | 984 | 902 | 919 | 1082 | 7 1090 | 1232 | 626 | 774 | 633 | 1689 |
| 18 | 947 | 927 | 850 | 1141 | 1003 | 1304 | 525 | 848 | 570 | 1702 |
| 20 | 888 | 963 | 753 | 1219 | 889 | 1402 | 400 | 936 | 494 | 1760 |
| 22 | 800 | 1020 | 600 | 1347 | 698 | 1566 | 6 167 | 1110 | 357 | 1872 |
| 24 | 683 | 1126 | 337 | 1117 | 6 393 | 7 1799 | 880 | 1302 | 4 211 | 6 1973 |
| 226 | 438 | 1294 | 4 960 | 1770 | 6 890 | 7 212 | 311 | 8 1720 | 4 870 | 6 1249 |
| 28 | 4 1795 | 1763 | 000 | A5 1487 | 5 800 | 1050 | 5 390 | 8 1310 | 450 | 1540 |

Maximum Load - 29.5 Kips

* Erratic readings

| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |

TABLE XIII

Data Sheet

Date: 19 April 1954
Test No.: 20 (continued)
Plate No.: 2
Strain Indicator
Serial No. D58130
Type K
G. F. Setting 2.01

B-Edge Conditions

Load Application - Pump Jacks
Gasket - Double Solder 1/16" diam.

Segments Shims

| Gage Load Kips | 1 | 3 | 5 | 7 | 9 |
|---|---|---|---|---|---|
| | Deflection - d(inches) | | | | |
| 1 | .218 | .276 | .296 | .265 | .289 |
| 10 | .295 | .268 | .302 | .294 | .314 |
| 15 | .225 | .322 | .371 | .317 | .342 |
| 20 | .257 | .373 | .429 | .404 | .384 |
| 24 | .309 | .468 | .522* | .522* | .457 |

* Limit of dial gage.

TABLE XIV

Data Sheet

Date: 21 April 1954
Test No.: 21
Plate No.: 3
Strain Indicator
Serial No. D58130
Type K
G.F. Setting 2.01

Load Application - Pump
Jacks
Bar - 3/4" (G)
Gasket - Single 3/32" solder

Segments
Shims

| Load Kips | Gage No. 1 | Gage No. 2 | Position from Vertical Centerline (on Horizontal Centerline) -24" | -18" | -12" | -6" | el | 6" | 12" | 18" | 24" |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | Strain Reading (μin./in.) | | Deflection (d') ( in. x 1000) | | | | | | | | |
| Zero | 8-542 | 8-769 | 65 | 86 | 85 | 82 | 64 | 60 | 40 | 30 | 05 |
| 2 | 534 | 762 | 57 | 89 | 83 | 73 | 50 | 43 | 26 | 17 | 03 |
| 4 | 521 | 760 | 55 | 84 | 76 | 67 | 42 | 33 | 15 | 9 | -05 |
| 6 | 507 | 760 | 55 | 82 | 75 | 65 | 36 | 12 | 14 | 9 | -02 |
| 8 | 489 | 761 | 55 | 81 | 76 | 66 | 37 | 30 | 12 | 8 | -- |
| 10 | 465 | 766 | 55 | 83 | 75 | 64 | 37 | 29 | 10 | 6 | -- |
| 12 | 437 | 771 | 55 | 82 | 74 | 61 | 34 | 24 | 8 | 4 | -- |
| 14 | 421 | 784 | 54 | 78 | 70 | 59 | 32 | 21 | 3 | 2 | -- |
| | | | x385 (Reset dial gage) | | | | | | | | |
| 16 | 398 | 794 | x384 | 405 | 396 | 384 | 357 | 343 | 325 | 324 | 317 |
| 18 | 365 | 810 | 383 | 403 | 391 | 356 | 350 | 337 | 320 | 320 | 314 |
| 20 | 327 | 831 | 382 | 400 | 383 | 372 | 342 | 328 | 311 | 313 | 310 |
| 22 | 271 | 868 | 380 | 394 | 378 | 360 | 330 | 316 | 300 | 306 | 307 |
| 24 | 200 7-1200 | 921 | 376 | 387 | 366 | 346 | 314 | 299 | 287 | 295 | 302 |
| 26 | 1082 | 1018 | 368 | 370 | 346 | 322 | 289 | 275 | 267 | 281 | 295 |
| 28 | 874 | 1192 | 356 | 340 | 305 | 275 | 235 | 222 | 224 | 252 | 282 |
| 30 | 057 | 1871 | 299 | 227 | 166 | 133 | 106 | 112 | 129 | 180 | 252 |

Maximum Load - 32,500 pounds

TABLE XV

Data Sheet

Date: 21 April 1954
Test No.: 22
Plate No.: 4
Strain Indicator
Serial No. D58130
Type K
G.F. Setting 2.01

Load Application - Pump Segments
Jacks Shims
Bar - 3/4" (G)
Gasket - Single 3/32" diameter solder

| Load Kips | Gage No. | | Position from Vertical Centerline (on Horizontal Centerline) | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | 1 | 2 | -24" | -18" | -12" | -6" | el | 6" | 12" | 18" | 24" |
| | Strain Reading ($\mu$in./in.) | | Deflection (d') (in. x 1000) | | | | | | | | |
| Zero | 8-1307 | 7-1142 | 266 | 225 | 171 | 120 | 102 | 107 | 154 | 168 | 241 |
| 2 | 1281 | 1147 | 256 | 215 | 160 | 131 | 94 | 95 | 141 | 167 | 238 |
| 4 | 1259 | 1156 | 252 | 203 | 152 | 105 | 88 | 86 | 134 | 159 | 235 |
| 6 | 1225 | 1171 | 252 | 200 | 146 | 105 | 80 | 84 | 131 | 159 | 235 |
| 8 | 1193 | 1188 | 247 | 195 | 140 | 99 | 72 | 76 | 128 | 152 | 235 |
| 10 | 1157 | 1210 | 247 | 188 | 129 | 86 | 65 | 70 | 124 | 153 | 235 |
| 12 | 1111 | 1234 | 242 | 180 | 120 | 83 | 56 | 60 | 114 | 147 | 231 |
| 14 | 1059 | 1269 | 236 | 171 | 106 | 70 | 42 | 55 | 109 | 144 | 229 |
| 16 | 1000 | 1302 | 230 | 160 | 92 | 50 | 31 | 40 | 98 | 138 | 225 |
| 18 | 930 | 1361 | 226 | 148 | 73 | 27 | 18 | 30 | 90 | 131 | 222 |
| 20 | 851 | 1416 | 217 | 130 | 56 | 12 | 0 | 8 | 72 | 119 | 218 |
| 22 | 741 | 1510 | 206 | 111 | 10 | -- | -- | -- | 58 | 105 | 214 |
| 24 | 598 | 1615 | | | | | | | | | |
| 26 | 410 | 1772 | | | | | | | | | |
| 28 | 042 | 1965 | | | | | | | | | |
| 30 | 7-250 | 8-1640 | | | | | | | | | |

Maximum Load - 33,500 pounds

TABLE XVI

Initial Unfairness of Specimens

| Location from vertical centerline (on horizontal centerline) | Plate No. 1 | 2 | 3 | 4 |
|---|---|---|---|---|
| | Initial deflection $d_o$ (in.) | | | |
| -24" | --- | .055 | .004 | --- |
| -18" | --- | .036 | -.002 | .066 |
| -15" | --- | .043 | --- | --- |
| -12" | --- | .053 | -.007 | .074 |
| - 9" | .085* | .057 | --- | --- |
| - 6" | --- | .057 | -.009 | .057 |
| - 3" | --- | .051 | --- | --- |
| Centerline | --- | .041 | -.008 | .071 |
| + 6 | --- | .037 | .002 | .066 |
| +12 | --- | .031 | .000 | .033 |
| +18 | --- | .041 | .005 | .020 |
| +24 | --- | .054 | .006 | .021 |

* Maximum deflection under gage numbers 17 and 18, 8.04" from vertical centerline, 1.32 above horizontal centerline.

## H. LITERATURE CITATIONS


1. Ballard, J. A., Lemmon, E. C., "An Investigation of the effects of Shear on the Compressive Strength of Plating", MIT Thesis, Course XIIIA, 1949.

2. Batdorf, S. B., Stein, M., "Critical Combinations of Shear and Direct Stress for Simply Supported Rectangular Flat Plates", NACA, TN-1223, 1947.

3. Batdorf, S. B., "Theories of Plastic Buckling", Jour. Aero. Sci., Vol. 16 #7, p. 405, July 1949.

4. Bengston, H. W., "Ship Plating Under Compression and Hydrostatic Pressure", Trans. SNAME, Vol. 47, p. 80, 1939.

5. Bijlaard, P. P., "Theory of the Plastic Stability of Thin Plates", Int. Ass'n of Bridge and Structural Engineers, Vol. 6, p. 45, 1940-41.

6. Bijlaard, P. P., "Theory and Tests on the Plastic Stability of Plates and Shells", Jour. Aero. Sci., Vol. 17, No. 9, p. 529, 1949.

7. Bleich, F. B., Ramsey, L. B., "A Design Manual on the Buckling Strength of Metal Structures", T and B Bull. No. 2-2, SNAME, 1951.

8. Bleich, F. B., Buckling Strength of Metal Structures, McGraw-Hill Book Co., 1952.

9. Budiansky, B., Hu, Pai C., "The Lagrangian Multiplier Method of Finding Upper and Power Limits to Critical Stresses of Clamped Plates", NACA, TN-1103, 1946.

10. Budiansky, B., Connor, R. W., "Buckling Stresses of Clamped Rectangular Flat Plates in Shear", NACA, TN-1559, 1948.

11. Budiansky, B., Connor, R. W., Stein, M., "Buckling in Shear of Continuous Flat Plates", NACA, TN-1565, 1948.

## 8. LITERATURE CITATIONS


1. Bullard, E. J., Jeffreys, H. G., "An Investigation of the effects of
Paper on the Compressive Strength of Plates", 317 Phoenix, Cambridge
Press, 1949.

2. Bullard, H. H., Jones, M., "Optimal Distribution of Paper and Screws
Across the Supply Supported Instrument Flat Plates", Vol. 3, 324-1321, 1947.

3. Bullard, H. H., "Theories of Plastic Buckling", Amer. Instr. Inst.,
Vol. 16 (7, p. 438, July 1949.

4. Bullard, H. H., "Early Plastic Under Compression and Symmetric Instrument", Phoen. Instr. Vol. 61, p. 69, 1938.

5. Bullard, H. H., "Theory of the Plastic Buckling of Thin Plates", Inst. Aero of Bridge and Structural Engineers, Vol. 6, p. 47, Lyngby.

6. Bullard, H. H., "Theory and Tests on the Plastic Buckling of Thin Metal", Amer. Aero. Soc., Vol. 17, No. 5, p. 309, 1949.

7. Bullard, H. H., Bullard, L. J., "A Bridge Manual on the Buckling Strength of Metal Structures", 1 and 2 Edit. Mc. Aug. Hill, 1953.

8. Bullard, H. H., Handbook of Light Structures, Volume-III Book One, 1954.

9. Bullard, H. H., Mc. Phi C., "The Compressive Buckling Method of Plating Edge and Inner Limits in Stiffened Elements of Flanged Plates", 1955, 324-1321, 1946.

10. Bullard, H., Jones, R. K., "Buckling Stresses of Flanged Rectangular Plate Plates", Mech., 18-1949, 1946.

11. Bullard, H., Jones, R. H., Hunt, M., "Buckling in Shear of Continuous Plates for Newly Supported Instrument Flat Plates", Mech., 324-1321, 1947.

12. Bullard, H. H., Jones, M., "Optimal Distribution of Shear and Screws Across for Newly Supported Instrument Flat Plates", Mech., 324-1321, 1947.

13. Bullard, H. H., "Theories of Plastic Buckling", Amer. Instr. Inst., Vol. 16 (7, p. 438, July 1949.

14. Bullard, H. H., "Early Plastic Under Compression and Symmetric Instrument", Phoen. Instr. Vol. 61, p. 69, 1938.

15. Bullard, H. H., "Theory of the Plastic Buckling of Thin Plates", Inst. Aero of Bridge and Structural Engineers, Vol. 6, p. 47, Lyngby.

16. Bullard, H. H., "Theory and Tests on the Plastic Buckling of Thin Metal", Amer. Aero. Soc., Vol. 17, No. 5, p. 309, 1949.

17. Bullard, H. H., Bullard, L. J., "A Bridge Manual on the Buckling Strength of Metal Structures", 1 and 2 Edit. Mc. Aug. Hill, 1953.

18. Bullard, H. H., Handbook of Light Structures, Volume-III Book One, 1954.

19. Bullard, H. H., Mc. Phi C., "The Compressive Buckling Method of Plating Edge and Inner Limits in Stiffened Elements of Flanged Plates", 1955, 324-1321, 1946.

20. Bullard, H., Jones, R. K., "Buckling Stresses of Flanged Rectangular Plate Plates", Mech., 18-1949, 1946.

21. Bullard, H., Jones, R. H., Hunt, M., "Buckling in Shear of Continuous Plates for Newly Supported Instrument Flat Plates", Mech., 324-1321, 1947.

12. Capozzoli, L. J., "Buckling of Compressed Rectangular Plates With Clamped Intermittent Edge Supports", MIT Course I Thesis, 1950.

13. Cox, H. L., "Buckling of Thin Plates in Compression", British A.R.C., R and M No. 1554, 1933.

14. Cox, H. L., Clenshaw, W. J., "The Strength of Ships' Plating", Institute of Engineers and Shipbuilders, Vol. 81, p. 17, 1937-38.

15. Cox, H. L., "The Buckling of a Flat Rectangular Plate Under Axial Compression and Its Behavior After Buckling", British A.R.C., R and M No. 2041, May, 1945.

16. Cox, H. L., "The Buckling of a Flat Plate Under Axial Compression and Its Behavior After Buckling", British A.R.C., R and M No. 2175, Oct., 1945.

17. Cox, H. L., "Note on the Southwell Method for Estimating Critical Loads", British A.R.C., R and M No. 2696, Feb., 1947.

18. Donnell, L. H., "On the Application of Southwell's Method for the Analysis of Buckling Tests", S. Timoshenko 60th Anniversary Volume, p. 27, 1938.

19. Frankland, J. M., "The Strength of Ship Plating Under Edge Compression", David Taylor Model Basin Report 469, 1940.

20. Gerard, G., "Secant Modulus Method for Determining Plate Instability Above the Proportional Limit", Jour. Aero. Sci., Vol. 13, p. 38, 1946.

21. Handelman, G. H., Prager, W., "Plastic Buckling of a Rectangular Plate Under Edge Thrusts", NACA, TN-1530, TR-946, 1948.

22. Heimerl, G. J., "Determination of Plate Compressive Strengths", NACA, TN-1480, 1947.

23. Hill, H. N., "Chart for Critical Compressive Stress of Flat Rectangular Plates", NACA, TN-773, 1940.

24. Duff, N. J., "Note on Inelastic Buckling", Jour. Aero. Sciences, Vol. 2, No. 2, p. 163, 1944.

25. Hopkins, H. G., Rao, B. V. S. C., "The Initial Buckling of Flat Rectangular Panels Under Combined Shear and Compression", British A.R.C., R and M No. 1965, 1943.

26. Ma, Pai C., Lundquist, E. E., Batdorf, S. B., "Effect of Small Deviations from Flatness on Effective Width and Buckling of Plates in Compression", NACA, TN-1124, 1946.

27. Ilyushin, A. A., "The Elasto-Plastic Stability of Plates", N.A.C.A., T.M. 1188, 1946.

28. Ilyushin, A. A., "Stability of Plates and Shells Beyond the Proportional Limit", N.A.C.A., T.M. 1116, Oct. 1947.

29. Kollbrunner, C. F., "Das Ausbuelen der auf einseitigen, gleichmassig verteillen Druck beanspruchten Platten in elastischen und plastischen Bereich", Zurich E.T.H. Inst. f. Baustatic No. 17, 1946.

30. Lahde, E., Wagner, H., "Experimental Studies of the Effective Width of Buckled Sheets", N.A.C.A. T.M. 814 (Transl), 1936.

31. Levy, S., "The Bending of Rectangular Plates with Large Deflections", N.A.C.A. T.M. 846, 1942.

32. Lundquist, E., Stowell, E., "Critical Compressive Stress for Flat Rectangular Plates Supported Along All Edges and Elastically Restrained Against Rotation Along the Unloaded Edges", N.A.C.A. T.R. 733, 1942.

33. Marguerre, K., "The Apparent Width of the Plate in Compression", N.A.C.A. T.M. 833 (Transl) 1937.

34. Moulbetsch, J. L., "Buckling of Compressed Rectangular Plates with Built-in Edges", Jour. Appl. Mech., Vol. 4, p. A-54, June, 1937.

35. Mitchell, E. H., "The Strength of Ships' Structure Under Compressive Stresses", Trans., I.N.A., Vol. 78, p. 21, 1936.

36. Montgomerie, J., "Experiments on the Compression of Samples of Deck Plating and the Application of the Results in Relation to the Thickness of Such Plating in Certain Conditions of Loading", Shipbuilder and Marine Engine Builder, Vol. 41, p. 213, April, 1934.

37. Muckle, W., "Resistance to Buckling of Light Alloy Plates", N.E. Coast Inst. Eng. and Shipb. Trans., Vol. 64, p. 223, March, 1948.

38. Peters, R. W., "Buckling Tests of Flat Rectangular Plates Under Combined Shear and Longitudinal Compression", N.A.C.A. T.N. 1790, 1948.

39. Pfingstag, P. W., Palmer, C. J., "Effect of End Fixity on the Strength of Plating in Compression", M.I.T. Course XIIIA Thesis, 1937.

40. Polychrone, D. A., "On The Buckling of Intermittently Supported Plates", M.I.T. Thesis, Course I, 1949.

41. Pride, R. A., Heimerl, G. J., "Plastic Buckling of Simply Supported Compressed Plates", N.A.C.A. T.N. 1817, 1949.

42. Rossell, H. E., "Strength of Plating in Compression", S.N.A.M.E., Trans., Vol. 43, p. 121, 1935.

43. Schmadel, G., "Knickung von Schiffsplatten", Werft Reederei Hafen, p. 461, 15 November, 1930.

44. Schmadel, G., "Strength of Transversely Stiffened Decks of Ships", Geo. Reissner Anniv. Vol., p. 256, 1949.

45. Schultz, F. E., Weschler, C. J., "Strength of Flat Plating Under Edge Compression", M.I.T. Thesis Course XIII, 1937.

46. Schuman, L., Back, G., "Strength of Rectangular Flat Plates Under Edge Compression", N.A.C.A. T.R. 356, 1930.

47. Sechler, E. E., "The Ultimate Strength of Thin Flat Sheets in Compression", Guggenheim Aeronautical Laboratory Pub. 27, California Institute of Technology, 1933.

48. Southwell, R. V., "On the Analysis of Experimental Observations in Problems of Elastic Stability", Proc. Roy. Soc. London, Ser. A, Vol. 135, p. 601, 1932.

49. Stowell, E. Z., Schwartz, E. B., "Critical Stress For an Infinitely Long Flat Plate with Elastic Restrained Edges Under Combined Shear and Direct Stress", N.A.C.A. W.R. L-340 (ARR - 3K13), 1943.

50. Stowell, E. Z., "Critical Shear Stress of an Infinitely Long Flat Plate with Equal Elastic Restraint Against Rotation Along Parallel Edges", N.A.C.A. W.R. L-476, (ARR - 3K12), 1943.

51. Stowell, E. Z., "A Unified Theory of Plastic Buckling of Columns and Plates", N.A.C.A. T.N. 898, 1948.

52. Stowell, E. Z., "Critical Shear Stress of an Infinitely Long Plate in the Plastic Region", N.A.C.A. T.N. 1681, 1948.

53. Stowell, E. Z., "Buckling Strength for Flat Plates and Sections", A.S.C.E., 1951.

54. Sweeney, R. J., "The Strength of Hull Plating Under Compression", U. S. Experimental Model Basin, Progress Reports 1 and 2, 1953.

55. Timoshenko, S., Theory of Elastic Stability, McGraw-Hill Book Co., 1936.

56. von Karman, T., Sechler, E. E., Donnell, L. H., "The Strength of Thin Plates in Compression", Transactions A. S. M. E., Vol. 54, APM-54-5-53, 1932.

57. Wang, Chi-Teh, "Non-linear Large Deflection Boundary Value Problems of Rectangular Plates", N.A.C.A. T.N. 1425, 1948.

58. Warren, S. F., "The Buckling of Thin Plates Subjected to Combined Loads", M.I.T. Thesis, Course I, 1947.

59. Yoshiki, M., "On the Buckling and Collapsing Strength of Ship's Hull Parts Under Compressive Load", Jap. Sci.,Rev., Vol. 1, p. 148, 1949-50.

60. Yoshiki, M. "A New Method to Determine the Critical Buckling Points of Rectangular Plates in Compression", International Congress of Applied Mechanics, Istanbul, 1952.

61. Yoshiki, M., Handbook of Elastic Stability, Corona Pub. Co., Tokyo, 1951.

Thesis
P56
25070
Pittman
On providing uniform edge compressive loads for wide flat plates.

Thesis
P56
25070
Pittman
On providing uniform edge compressive loads for wide flat plates.

thesP56
On providing uniform edge compressive lo
3 2768 001 92434 3
DUDLEY KNOX LIBRARY